

An OMG[®] Unified Architecture Framework[®] Domain Metamodel Publication



UAF[®]

OMG UNIFIED
ARCHITECTURE
FRAMEWORK[®]

Unified Architecture Framework (UAF) Domain Metamodel

Version 1.1

OMG Document Number: formal/19-11-05

Release Date: April 2020

Standard document URL: <https://www.omg.org/spec/UAF/1.1>

Normative Machine Consumable File(s):

<https://www.omg.org/spec/UAF/20190615/UAF.xmi>

https://www.omg.org/spec/UAF/20190615/Measurements_Library.xmi

Copyright © 2019, IBM

Copyright © 2019, KDM Analytics

Copyright © 2019, Mega

Copyright © 2020, Object Management Group, Inc.

Copyright © 2019, No Magic Inc. a Dassault Systemes Company

Copyright © 2019, PTC

Copyright © 2019, Sparx Systems

USE OF SPECIFICATION - TERMS, CONDITIONS & NOTICES

The material in this document details an Object Management Group specification in accordance with the terms, conditions and notices set forth below. This document does not represent a commitment to implement any portion of this specification in any company's products. The information contained in this document is subject to change without notice.

LICENSES

The companies listed above have granted to the Object Management Group, Inc. (OMG) a nonexclusive, royalty-free, paid up, worldwide license to copy and distribute this document and to modify this document and distribute copies of the modified version. Each of the copyright holders listed above has agreed that no person shall be deemed to have infringed the copyright in the included material of any such copyright holder by reason of having used the specification set forth herein or having conformed any computer software to the specification.

Subject to all of the terms and conditions below, the owners of the copyright in this specification hereby grant you a fully-paid up, non-exclusive, nontransferable, perpetual, worldwide license (without the right to sublicense), to use this specification to create and distribute software and special purpose specifications that are based upon this specification, and to use, copy, and distribute this specification as provided under the Copyright Act; provided that: (1) both the copyright notice identified above and this permission notice appear on any copies of this specification; (2) the use of the specifications is for informational purposes and will not be copied or posted on any network computer or broadcast in any media and will not be otherwise resold or transferred for commercial purposes; and (3) no modifications are made to this specification. This limited permission automatically terminates without notice if you breach any of these terms or conditions. Upon termination, you will destroy immediately any copies of the specifications in your possession or control.

PATENTS

The attention of adopters is directed to the possibility that compliance with or adoption of OMG specifications may require use of an invention covered by patent rights. OMG shall not be responsible for identifying patents for which a license may be required by any OMG specification, or for conducting legal inquiries into the legal validity or scope of those patents that are brought to its attention. OMG specifications are prospective and advisory only. Prospective users are responsible for protecting themselves against liability for infringement of patents.

GENERAL USE RESTRICTIONS

Any unauthorized use of this specification may violate copyright laws, trademark laws, and communications regulations and statutes. This document contains information which is protected by copyright. All Rights Reserved. No part of this work covered by copyright herein may be reproduced or used in any form or by any

means--graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems--without permission of the copyright owner.

DISCLAIMER OF WARRANTY

WHILE THIS PUBLICATION IS BELIEVED TO BE ACCURATE, IT IS PROVIDED "AS IS" AND MAY CONTAIN ERRORS OR MISPRINTS. THE OBJECT MANAGEMENT GROUP AND THE COMPANIES LISTED ABOVE MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS PUBLICATION, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF TITLE OR OWNERSHIP, IMPLIED WARRANTY OF MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR USE. IN NO EVENT SHALL THE OBJECT MANAGEMENT GROUP OR ANY OF THE COMPANIES LISTED ABOVE BE LIABLE FOR ERRORS CONTAINED HEREIN OR FOR DIRECT, INDIRECT, INCIDENTAL, SPECIAL, CONSEQUENTIAL, RELIANCE OR COVER DAMAGES, INCLUDING LOSS OF PROFITS, REVENUE, DATA OR USE, INCURRED BY ANY USER OR ANY THIRD PARTY IN CONNECTION WITH THE FURNISHING, PERFORMANCE, OR USE OF THIS MATERIAL, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

The entire risk as to the quality and performance of software developed using this specification is borne by you. This disclaimer of warranty constitutes an essential part of the license granted to you to use this specification.

RESTRICTED RIGHTS LEGEND

Use, duplication or disclosure by the U.S. Government is subject to the restrictions set forth in subparagraph (c) (1) (ii) of The Rights in Technical Data and Computer Software Clause at DFARS 252.227-7013 or in subparagraph (c)(1) and (2) of the Commercial Computer Software - Restricted Rights clauses at 48 C.F.R. 52.227-19 or as specified in 48 C.F.R. 227-7202-2 of the DoD F.A.R. Supplement and its successors, or as specified in 48 C.F.R. 12.212 of the Federal Acquisition Regulations and its successors, as applicable. The specification copyright owners are as indicated above and may be contacted through the Object Management Group, 109 Highland Avenue, Needham, MA 02494, U.S.A.

TRADEMARKS

CORBA®, CORBA logos®, FIBO®, Financial Industry Business Ontology®, FINANCIAL INSTRUMENT GLOBAL IDENTIFIER®, IIOP®, IMM®, Model Driven Architecture®, MDA®, Object Management Group®, OMG®, OMG Logo®, SoaML®, SOAML®, SysML®, UAF®, Unified Modeling Language®, UML®, UML Cube Logo®, VSIPL®, and XMI® are registered trademarks of the Object Management Group, Inc.

For a complete list of trademarks, see: https://www.omg.org/legal/tm_list.htm. All other products or company names mentioned are used for identification purposes only, and may be trademarks of their respective owners.

COMPLIANCE

The copyright holders listed above acknowledge that the Object Management Group (acting itself or through its designees) is and shall at all times be the sole entity that may authorize developers, suppliers and sellers of computer software to use certification marks, trademarks or other special designations to indicate compliance with these materials.

Software developed under the terms of this license may claim compliance or conformance with this specification if and only if the software compliance is of a nature fully matching the applicable compliance points as stated in the specification. Software developed only partially matching the applicable compliance points may claim only that the software was based on this specification, but may not claim compliance or conformance with this specification. In the event that testing suites are implemented or approved by Object Management Group, Inc., software developed using this specification may claim compliance or conformance with the specification only if the software satisfactorily completes the testing suites.

Table of Contents

PREFACE	1
1. SCOPE	3
1.1 INTRODUCTION	3
1.2 UAF BACKGROUND	3
1.3 INTENDED USAGE	4
1.4 RELATED DOCUMENTS.....	4
2. CONFORMANCE	5
3. REFERENCES.....	6
3.1 NORMATIVE REFERENCES.....	6
3.2 OMG DOCUMENTS (NORMATIVE REFERENCES).....	6
3.3 OTHER NORMATIVE REFERENCES.....	6
3.4 INFORMATIVE REFERENCES.....	7
4. TERMS AND DEFINITIONS.....	8
5. SYMBOLS	9
6. ADDITIONAL INFORMATION.....	11
6.1 CHANGES TO ADOPTED OMG SPECIFICATIONS.....	11
6.2 LANGUAGE ARCHITECTURE	11
6.3 PHILOSOPHY	11
6.4 CORE PRINCIPLES.....	11
7. UAF GRID	13
7.1 DESCRIPTIONS OF DOMAINS AND MODEL KINDS.....	15
7.2 DOMAIN INTERRELATIONSHIPS	17
8. DOMAIN METAMODEL DIAGRAM LEGEND	17
9. DOMAIN METAMODEL DIAGRAMS.....	19
9.1 VIEW SPECIFICATIONS	19
9.1.1 <i>View Specifications::Metadata</i>	19
9.1.2 <i>View Specifications::Strategic</i>	20
9.1.3 <i>View Specifications::Operational</i>	28
9.1.4 <i>View Specifications::Services</i>	38
9.1.5 <i>View Specifications::Personnel</i>	47
9.1.6 <i>View Specifications::Resources</i>	62
9.1.7 <i>View Specifications::Security</i>	74
9.1.8 <i>View Specifications::Projects</i>	82
9.1.9 <i>View Specifications::Standards</i>	88
9.1.10 <i>View Specifications::Actual Resources</i>	91
9.1.11 <i>View Specifications::Dictionary</i>	94
9.1.12 <i>View Specifications::Summary & Overview</i>	95
9.1.13 <i>View Specifications::Requirements</i>	96
9.1.14 <i>View Specifications::Information</i>	97
9.1.15 <i>View Specifications::Parameters</i>	98
9.1.16 <i>View Specifications::Other</i>	101

10.	DOMAIN METAMODEL (DMM) ELEMENTS	105
10.1	DOMAIN METAMODEL.....	105
10.1.1	<i>Domain MetaModel::Metadata</i>	105
10.1.2	<i>Domain MetaModel::Strategic</i>	119
10.1.3	<i>Domain MetaModel::Operational</i>	130
10.1.4	<i>Domain MetaModel::Services</i>	144
10.1.5	<i>Domain MetaModel::Personnel</i>	152
10.1.6	<i>Domain MetaModel::Resources</i>	159
10.1.7	<i>Domain MetaModel::Security</i>	177
10.1.8	<i>Domain MetaModel::Projects</i>	192
10.1.9	<i>Domain MetaModel::Standards</i>	199
10.1.10	<i>Domain MetaModel::Actual Resources</i>	201
10.1.11	<i>Domain MetaModel::Dictionary</i>	207
10.1.12	<i>Domain MetaModel::Summary & Overview</i>	209
10.1.13	<i>Domain MetaModel::Information</i>	213
10.1.14	<i>Domain MetaModel::Parameters</i>	214

TABLE OF FIGURES

Figure 7:1- UAF Grid.....	13
Figure 7:2 - Domain Interrelationships.....	17
Figure 7:3 - Legend of color codes for element types defined in UAF	18
Figure 8:2 - Strategic Structure.....	22
Figure 8:3 - Strategic Connectivity.....	23
Figure 8:4 - Strategic States.....	24
Figure 8:5 - Strategic Constraints	25
Figure 8:6 - Strategic Roadmap: Deployment	26
Figure 8:7 - Strategic Roadmap: Phasing	27
Figure 8:8 - Strategic Traceability	28
Figure 8:9 - Operational Taxonomy	29
Figure 8:10 - Operational Structure.....	30
Figure 8:11 - Operational Connectivity.....	31
Figure 8:12 - Operational Processes	32
Figure 8:13 - Operational Processes BPMN Semantics.....	34
Figure 8:14 - Operational States	35
Figure 8:15 - Operational Interaction Scenarios.....	36
Figure 8:16 - Operational Constraints	37
Figure 8:17 - Operational Traceability	38
Figure 8:18 - Services Taxonomy.....	39
Figure 8:19 - Services Structure	40
Figure 8:20 - Services Connectivity	41
Figure 8:21 - Services Processes	42
Figure 8:22 - Services Processes BPMN Semantics.....	43
Figure 8:23 - Services States	44
Figure 8:24 - Services Interaction Scenarios	45
Figure 8:25 - Services Constraints.....	46
Figure 8:26 - Services Roadmap.....	46
Figure 8:27 - Services Traceability.....	47
Figure 8:28 - Personnel Taxonomy	48
Figure 8:29 - Personnel Structure	49
Figure 8:30 - Personnel Connectivity	50
Figure 8:31 - Personnel Processes	51
Figure 8:32 - Personnel States	52
Figure 8:33 - Personnel Interaction Scenarios.....	53
Figure 8:34 - Personnel Constraints: Competence.....	55
Figure 8:35 - Personnel Constraints: Drivers.....	56
Figure 8:36 - Personnel Constraints: Performance	57
Figure 8:37 - Personnel Roadmap: Availability	59
Figure 8:38 - Personnel Roadmap: Evolution.....	60
Figure 8:39 - Personnel Roadmap: Forecast.....	61
Figure 8:40 - Personnel Traceability	62
Figure 8:41 - Resources Taxonomy.....	63
Figure 8:42 - Resources Structure	64
Figure 8:43 - Resources Connectivity	65
Figure 8:44 - Resources Processes	67
Figure 8:45 - Resources Processes BPMN Semantics.....	68
Figure 8:46 - Resources States	69
Figure 8:47 - Resources Interaction Scenarios	70
Figure 8:48 - Resources Constraints.....	71
Figure 8:49 - Resources Roadmap: Evolution.....	72

Figure 8:50 - Resources Roadmap: Forecast	73
Figure 8:51 - Resources Traceability	74
Figure 8:52 - Security Taxonomy	75
Figure 8:53 - Security Structure	76
Figure 8:54 - Security Connectivity	77
Figure 8:55 - Security Processes	79
Figure 8:56 - Security Constraints	80
Figure 8:57 - Security Traceability	82
Figure 8:58 - Project Taxonomy	83
Figure 8:59 - Project Structure	84
Figure 8:60 - Project Connectivity	85
Figure 8:61 - Project Processes	86
Figure 8:62 - Project Roadmap	87
Figure 8:63 - Project Traceability	88
Figure 8:64 - Standards Taxonomy	89
Figure 8:65 - Standards Structure	90
Figure 8:66 - Standards Roadmap	90
Figure 8:67 - Standards Traceability	91
Figure 8:68 - Actual Resources Structure	92
Figure 8:69 - Actual Resources Connectivity	93
Figure 8:70 - Actual Resources Traceability	94
Figure 8:71 - Dictionary	95
Figure 8:72 - Summary & Overview	96
Figure 8:73 - Requirements	97
Figure 8:74 - Information Model	98
Figure 8:75 - Parameters: Environment	99
Figure 8:76 - Parameters: Measurements	100
Figure 8:77 - BPMN	101
Figure 8:78 - IEPPV	102
Figure 8:79 - NIEM	103
Figure 9:1 - ArchitectureMetadata	105
Figure 9:2 - InteractionScenarioGeneralization	106
Figure 9:3 - Metadata	106
Figure 9:4 - ProcessGeneralization	107
Figure 9:5 - PropertySetGeneralization	107
Figure 9:6 - StateDescriptionGeneralization	108
Figure 9:7 - EnvironmentProperty	108
Figure 9:8 - Exchange	109
Figure 9:9 - ExchangeItem	109
Figure 9:10 - Resource	110
Figure 9:11 - ActivityPerformableUnderCondition	110
Figure 9:12 - IsCapableToPerform	111
Figure 9:13 - PerformsInContext	111
Figure 9:14 - Process	112
Figure 9:15 - Process	112
Figure 9:16 - ProcessEdge	113
Figure 9:17 - ProcessOperation	113
Figure 9:18 - ProcessParameter	114
Figure 9:19 - ProcessUsage	114
Figure 9:20 - StateDescription	115
Figure 9:21 - InteractionRole	115
Figure 9:22 - InteractionScenario	116
Figure 9:23 - Information	117
Figure 9:24 - Rule	117

Figure 9:25 - ArchitecturalReference	118
Figure 9:26 - Implements.....	119
Figure 9:27 - Capability.....	120
Figure 9:28 - CapabilityGeneralization	120
Figure 9:29 - ActualEnduringTask	121
Figure 9:30 - ActualEnterprisePhase	121
Figure 9:31 - CapabilityRole	122
Figure 9:32 - EnduringTask.....	122
Figure 9:33 - EnterpriseGoal	122
Figure 9:34 - EnterprisePhase.....	123
Figure 9:35 - EnterpriseVision	123
Figure 9:36 - StructuralPart	124
Figure 9:37 - TemporalPart	124
Figure 9:38 - VisionStatement.....	125
Figure 9:39 - WholeLifeEnterprise.....	125
Figure 9:40 - CapabilityDependency	125
Figure 9:41 - CapabilityRoleDependency	126
Figure 9:42 - AchievedEffect	126
Figure 9:43 - Achiever.....	127
Figure 9:44 - DesiredEffect	127
Figure 9:45 - Desirer.....	128
Figure 9:46 - CapabilityForTask	128
Figure 9:47 - CapableElement.....	129
Figure 9:48 - Exhibits.....	129
Figure 9:49 - MapsToCapability	130
Figure 9:50 - OrganizationInEnterprise.....	130
Figure 9:51 - ArbitraryConnector.....	131
Figure 9:52 - ConceptItem.....	131
Figure 9:53 - HighLevelOperationalConcept	132
Figure 9:54 - KnownResource.....	132
Figure 9:55 - OperationalAgent.....	133
Figure 9:56 - OperationalArchitecture.....	133
Figure 9:57 - OperationalMethod	134
Figure 9:58 - OperationalParameter	134
Figure 9:59 - OperationalPerformer	135
Figure 9:60 - OperationalRole.....	135
Figure 9:61 - ProblemDomain.....	136
Figure 9:62 - OperationalConnector.....	136
Figure 9:63 - OperationalExchange.....	137
Figure 9:64 - OperationalExchangeItem.....	137
Figure 9:65 - OperationalInterface	138
Figure 9:66 - OperationalPort.....	138
Figure 9:67 - OperationalSignal	139
Figure 9:68 - OperationalActivity	139
Figure 9:69 - OperationalActivityAction.....	140
Figure 9:70 - OperationalActivityEdge	140
Figure 9:71 - StandardOperationalActivity	141
Figure 9:72 - OperationalStateDescription.....	141
Figure 9:73 - OperationalInteractionScenario	142
Figure 9:74 - OperationalMessage.....	142
Figure 9:75 - InformationElement.....	143
Figure 9:76 - OperationalConstraint.....	143
Figure 9:77 - SubjectOfOperationalConstraint.....	143
Figure 9:78 - ServiceSpecification	144

Figure 9:79 - ServiceSpecificationGeneralization	145
Figure 9:80 - ServiceConnector	145
Figure 9:81 - ServiceMethod	146
Figure 9:82 - ServiceParameter	146
Figure 9:83 - ServiceSpecificationRole	147
Figure 9:84 - ServiceInterface	147
Figure 9:85 - ServicePort	148
Figure 9:86 - ServiceFunction	148
Figure 9:87 - ServiceFunctionAction	149
Figure 9:88 - ServiceFunctionEdge	149
Figure 9:89 - ServiceStateDescription	150
Figure 9:90 - ServiceInteractionScenario	150
Figure 9:91 - ServiceMessage	151
Figure 9:92 - ServicePolicy	151
Figure 9:93 - Consumes	152
Figure 9:94 - Organization	152
Figure 9:95 - OrganizationalResource	153
Figure 9:96 - Person	153
Figure 9:97 - Post	154
Figure 9:98 - Responsibility	154
Figure 9:99 - PostRole	155
Figure 9:100 - SubOrganization	155
Figure 9:101 - Command	156
Figure 9:102 - Control	156
Figure 9:103 - ResourceInteractionScenario	157
Figure 9:104 - Competence	157
Figure 9:105 - CompetenceForRole	158
Figure 9:106 - RequiresCompetence	158
Figure 9:107 - FillsPost	159
Figure 9:108 - CompetenceToConduct	159
Figure 9:109 - CapabilityConfiguration	160
Figure 9:110 - NaturalResource	160
Figure 9:111 - PhysicalResource	160
Figure 9:112 - ResourceArchitecture	161
Figure 9:113 - ResourceArtifact	161
Figure 9:114 - ResourcePerformer	162
Figure 9:115 - Software	162
Figure 9:116 - System	163
Figure 9:117 - ResourceMethod	163
Figure 9:118 - ResourceParameter	164
Figure 9:119 - ResourcePort	164
Figure 9:120 - ResourceRole	165
Figure 9:121 - ResourceConnector	166
Figure 9:122 - ResourceExchange	166
Figure 9:123 - ResourceExchangeItem	167
Figure 9:124 - ResourceInterface	168
Figure 9:125 - ResourceSignal	168
Figure 9:126 - Function	169
Figure 9:127 - FunctionAction	169
Figure 9:128 - FunctionEdge	170
Figure 9:129 - ResourceStateDescription	170
Figure 9:130 - ResourceMessage	171
Figure 9:131 - DataElement	171
Figure 9:132 - DataRole	172

Figure 9:133 - ResourceConstraint.....	172
Figure 9:134 - SubjectOfResourceConstraint.....	173
Figure 9:135 - Forecast.....	173
Figure 9:136 - SubjectOfForecast.....	174
Figure 9:137 - Technology.....	174
Figure 9:138 - VersionedElement.....	175
Figure 9:139 - VersionOfConfiguration.....	175
Figure 9:140 - VersionSuccession.....	176
Figure 9:141 - WholeLifeConfiguration.....	176
Figure 9:142 - ProtocolImplementation.....	177
Figure 9:143 - Asset.....	178
Figure 9:144 - OperationalAsset.....	178
Figure 9:145 - OperationalMitigation.....	179
Figure 9:146 - ResourceAsset.....	179
Figure 9:147 - ResourceMitigation.....	179
Figure 9:148 - SecurityEnclave.....	180
Figure 9:149 - AssetRole.....	180
Figure 9:150 - InformationRole.....	181
Figure 9:151 - EnhancedSecurityControl.....	181
Figure 9:152 - Enhances.....	182
Figure 9:153 - Protects.....	182
Figure 9:154 - ProtectsInContext.....	183
Figure 9:155 - SecurityProcess.....	183
Figure 9:156 - SecurityProcessAction.....	184
Figure 9:157 - ActualRisk.....	184
Figure 9:158 - Caveat.....	185
Figure 9:159 - Risk.....	185
Figure 9:160 - SecurityAvailability.....	185
Figure 9:161 - SecurityCategory.....	186
Figure 9:162 - SecurityClassification.....	186
Figure 9:163 - SecurityClassificationKind.....	187
Figure 9:164 - SecurityConstraint.....	187
Figure 9:165 - SecurityControl.....	188
Figure 9:166 - SecurityControlFamily.....	188
Figure 9:167 - SecurityIntegrity.....	189
Figure 9:168 - SecurityMeasurement.....	189
Figure 9:169 - SubjectOfSecurityConstraint.....	190
Figure 9:170 - Affects.....	190
Figure 9:171 - AffectsInContext.....	190
Figure 9:172 - Mitigates.....	191
Figure 9:173 - OwnsRisk.....	191
Figure 9:174 - OwnsRiskInContext.....	192
Figure 9:175 - Project.....	192
Figure 9:176 - ProjectMilestone.....	193
Figure 9:177 - ActualProjectMilestoneRole.....	193
Figure 9:178 - ProjectMilestoneRole.....	194
Figure 9:179 - ProjectStatus.....	194
Figure 9:180 - ProjectTheme.....	195
Figure 9:181 - StatusIndicators.....	195
Figure 9:182 - MilestoneDependency.....	196
Figure 9:183 - ProjectActivity.....	196
Figure 9:184 - ProjectActivityAction.....	196
Figure 9:185 - ProjectSequence.....	197
Figure 9:186 - ActualProject.....	197

Figure 9:187 - ActualProjectMilestone.....	198
Figure 9:188 - ResponsibleFor	199
Figure 9:189 - Protocol.....	199
Figure 9:190 - ProtocolStack	200
Figure 9:191 - Standard	200
Figure 9:192 - ProtocolLayer.....	201
Figure 9:193 - ActualOrganization	201
Figure 9:194 - ActualOrganizationalResource	202
Figure 9:195 - ActualPerson	202
Figure 9:196 - ActualPost.....	203
Figure 9:197 - ActualResource	203
Figure 9:198 - ActualResourceRelationship.....	204
Figure 9:199 - ActualResponsibility	204
Figure 9:200 - ActualResponsibleResource.....	205
Figure 9:201 - FieldedCapability	205
Figure 9:202 - ActualService.....	206
Figure 9:203 - ProvidedServiceLevel	206
Figure 9:204 - ProvidesCompetence.....	206
Figure 9:205 - RequiredServiceLevel.....	207
Figure 9:206 - Alias	207
Figure 9:207 - Definition	208
Figure 9:208 - SameAs	208
Figure 9:209 - ArchitecturalDescription	209
Figure 9:210 - Architecture	210
Figure 9:211 - Concern	211
Figure 9:212 - Stakeholder	211
Figure 9:213 - UAFElement	212
Figure 9:214 - View.....	212
Figure 9:215 - Viewpoint	213
Figure 9:216 - DataModel	213
Figure 9:217 - ActualCondition.....	214
Figure 9:218 - ActualEnvironment.....	214
Figure 9:219 - ActualLocation.....	215
Figure 9:220 - ActualMeasurement	216
Figure 9:221 - ActualMeasurementSet.....	216
Figure 9:222 - ActualPropertySet.....	217
Figure 9:223 - ActualState.....	217
Figure 9:224 - Condition	218
Figure 9:225 - Environment.....	218
Figure 9:226 - GeoPoliticalExtentType	219
Figure 9:227 - ISO8601DateTime	219
Figure 9:228 - Location	220
Figure 9:229 - LocationHolder	220
Figure 9:230 - MeasurableElement.....	221
Figure 9:231 - Measurement.....	222
Figure 9:232 - MeasurementSet.....	222
Figure 9:233 - PropertySet.....	223

TABLE OF TABLES

Table 1:1 - Table of Related Documents	4
Table 5:1 - Description of acronyms used in this specification	9
Table 7:1 - Definitions for the Domains	15
Table 7:2 - Definitions of the Model Kinds	16

Preface

OMG

Founded in 1989, the Object Management Group, Inc. (OMG) is an open membership, not-for-profit computer industry standards consortium that produces and maintains computer industry specifications for interoperable, portable and reusable enterprise applications in distributed, heterogeneous environments. Membership includes Information Technology vendors, end users, government agencies and academia. OMG member companies write, adopt, and maintain its specifications following a mature, open process. OMG's specifications implement the Model Driven Architecture® (MDA®), maximizing ROI through a full-lifecycle approach to enterprise integration that covers multiple operating systems, programming languages, middleware and networking infrastructures, and software development environments. OMG's specifications include: UML® (Unified Modeling Language™); CORBA® (Common Object Request Broker Architecture); CWM™ (Common Warehouse Metamodel); and industry-specific standards for dozens of vertical markets. More information on the OMG is available at <https://www.omg.org/>.

OMG Specifications

As noted, OMG specifications address middleware, modeling and vertical domain frameworks. All OMG Specifications are available from this URL: <https://www.omg.org/spec>

Specifications are organized by the following categories:

Business Modeling Specifications^[1]_{SEP}

Middleware Specifications

- CORBA/IIOP
- Data Distribution Services
- Specialized CORBA IDL/Language Mapping Specifications

Modeling and Metadata Specifications

- UML, MOF, CWM, XMI
- UML Profile Specifications

Platform Independent Model (PIM) - Platform Specific Model (PSM) - Interface Specifications

- CORBAServices
- CORBAFacilities
- OMG Domain Specifications
- CORBA Embedded Intelligence Specifications
- CORBA Security Specifications

All of OMG's formal specifications may be downloaded without charge from our website. (Products implementing OMG specifications are available from individual suppliers.) Copies of specifications, available in PostScript and PDF format, may be obtained from the Specifications Catalog cited above or by contacting the Object Management Group, Inc. at: OMG Headquarters 109 Highland Avenue, Needham, MA 02494 USA Tel: +1- 781-444-0404 Fax: +1-781-444-0320 Email: pubs@omg.org

Certain OMG specifications are also available as ISO standards. Please consult <http://www.iso.org>

Typographical Conventions

The type styles shown below are used in this document to distinguish programming statements from ordinary English. However, these conventions are not used in tables or section headings where no distinction is necessary.

Times/Times New Roman - 10 pt.: Standard body text

Helvetica/Arial - 10 pt. Bold: OMG Interface Definition Language (OMG IDL) and syntax elements.

Courier - 10 pt. Bold: Programming language elements.

Helvetica/Arial - 10 pt: Exceptions

Note – Terms that appear in *italics* are defined in the glossary. Italic text also represents the name of a document, specification, or other publication.

Issues

All OMG specifications are subject to continuous review and improvement. As part of this process we encourage readers to report any ambiguities, inconsistencies, or inaccuracies they may find by completing the Issue Reporting Form listed on the main web page <https://www.omg.org>, under Documents, Report a Bug/Issue (<https://issues.omg.org/issues/create-new-issue>).

1 Scope

1.1 Introduction

There are four parts to this specification, two are normative and two informative. The normative parts are:

1. The UAF Domain Metamodel (DMM) (this document) that provides the definition of concepts, relationships and viewpoints for the framework. The UAF DMM is the basis for any implementation of UAF including non-UML/SysML implementations.
2. The UAF Profile (UAFP) (see document dtc/19-06-15) is a UML/SysML implementation of the UAF DMM

The informative parts are:

3. The UAF Traceability, Annex A (see document dtc/19-06-17), which details the mappings between the UAF and the various frameworks and languages that contribute to the UAF.
4. The UAF Example Model, Annex B (see document dtc/19-06-18), which illustrates a practical usage of UAF.

1.2 UAF Background

UAF evolved from the Unified Profile for DoDAF and MODAF (UPDM), version 2.1. UAF extends the scope of UPDM and generalizes it to make it applicable to commercial as well as military architectures. The intent of UAF is to provide a standard representation for describing enterprise architectures using a Model Based Systems Engineering (MBSE) approach.

The core concepts in the UAF are based upon the DoDAF 2.0.2 Domain Metamodel (DM2) and the MODAF ontological data exchange mechanism (MODEM), Security Views from Canada's Department of National Defense Architecture Framework (DNDAF) and the North Atlantic Treaty Organization (NATO) Architecture Framework (NAF) v 4.

UAF models describe a system¹ from a set of stakeholders' concerns such as security or information through a set of predefined viewpoints. Developed models can also reflect custom viewpoints or users can develop more formal extensions for new viewpoints.

The UAFP can be used to develop architectures compliant with:

- Department of Defense Architecture Framework (DoDAF) version 2.02
- Ministry of Defence Architecture Framework (MODAF) version 1.3
- North Atlantic Treaty Organization (NATO) Architecture Framework (NAF) version 3.1
- North Atlantic Treaty Organization (NATO) Architecture Framework (NAF) version 4

UAF v 1.1 supports the capability to:

- model architectures for a broad range of complex systems, which may include hardware, software, data, personnel, and facility elements,
- model consistent architectures for system-of-systems (SoS) down to lower levels of design and implementation,
- support the analysis, specification, design, and verification of complex systems; and
- improve the ability to exchange architecture information among related tools that are SysML based.

¹ The term system is used from: "Systems and software engineering -- Architecture description," http://www.iso.org/iso/catalogue_detail.htm?csnumber=50508

1.3 Intended Usage

The UAF enables the modeling of strategic capabilities, operational scenarios, services, resources, personnel, security, projects, standards, measures and requirements; which supports best practices through, separation of concerns and abstractions. In addition, the UAF enables the modeling of related architecture concepts such as:

- System of Systems (SoS),
- information exchanges consistent with the National Information Exchange Model (NIEM),
- DoD's doctrine, organization, training material, leadership & education, personnel, and facilities (DOTMLPF)
- UK Ministry of Defence Lines of Development (DLOD) elements,
- Human Computer Interfaces (HCI).

Further, The UAF conforms to terms defined in the ISO/IEC/IEEE 42010 standard for architecture description, where the terms: architecture, architecture description (AD), architecture framework, architecture view, architecture viewpoint, concern, environment, model kind, stakeholder [ISO/IEC/IEEE 42010:2011] form correspondence rules specified as constraints on UAF.

1.4 Related Documents

The specification includes a metamodel and description as separate documents. Other appendices are also provided as separate documents. The table below provides a listing of these documents:

Table 1:1 - Table of Related Documents

dtc/19-06-16	The UAF Domain MetaModel (DMM)
dtc/19-06-15	The UAF Profile (UAFP)
dtc/19-06-17	Appendix A that contains a separate traceability subsection from UAFP to each of the frameworks listed in Section 1.2 of this specification
dtc/19-06-18	Appendix B: An example of how the language can be used to represent a UAFP architecture
dtc/19-06-19	UAF XMI file
dtc/19-06-20	UAF XMI Measurements library
dtc/19-05-14	Attachments

2 Conformance

UAF specifies four types of conformance.

Type 1 Conformance: - UAF View specification conformance. A tool demonstrating view specification conformance shall implement a version of all the view specifications defined in the UAF Grid, with the exception of the view specifications in the Metadata Domain. Optionally the tool vendor can implement other donor framework viewpoints, for instance DoDAF, MODAF or NAF based upon the mapping between them and UAF provided in Appendix A (dtc/19-06-17)

Type 2 Conformance: - UAF Conceptual Syntax Conformance. A tool demonstrating conceptual syntax conformance is consistent with the concepts, relationships and constraints defined in the UAF DMM (this document). UAF Conceptual Syntax Conformance implies Type 1 Conformance.

Type 3 Conformance: - UAF Formal Syntax Conformance. A tool demonstrating formal syntax conformance:

- enables instances of concrete UAFP stereotypes defined in the UAFP (dtc/19-06-15)
- complies with the constraints defined in the UAFP (dtc/19-06-15)
- complies with the SysML version 1.5 Concrete Syntax Conformance (formal/17-05-01)

UAF Formal Syntax Conformance implies Type 2 Conformance.

Type 4 Conformance: - UAF Model interchange conformance. A tool demonstrating model interchange conformance can import and export conformant XMI for all valid UAFP models. Model interchange conformance implies Type 3 Conformance.

3 References

3.1 Normative References

The following normative documents contain provisions which, through reference in this text, constitute provisions of this specification. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply.

3.2 OMG Documents (Normative References)

- Unified Modeling Language (UML), 2.5.1, December 2017, <https://www.omg.org/spec/UML>
- Object Constraint Language (OCL), 2.4, February 2014, <https://www.omg.org/spec/OCL>
- System Modeling Language (SysML) ,1.5, May 2017, <https://www.omg.org/spec/SysML>
- Diagram Definition (DD), 1.1, June 2015, <https://www.omg.org/spec/DD>
- UML Profile for the National Information Exchange Model (NIEM UML), 3.0, April 2017, <https://www.omg.org/spec/NIEM-UML>
- Unified Profile for DoDAF and MODAF (UPDM), 2.1, August 2013, <https://www.omg.org/spec/UPDM>
- UML Profile for BPMN Processes, 1.0, July 2014, <https://www.omg.org/spec/BPMNProfile>
- Ontology Definition Metamodel (ODM), 1.1, September 2014, <https://www.omg.org/spec/ODM>
- Information Exchange Packaging Policy Vocabulary (IEPPV) 1.0, May 2015, <https://www.omg.org/spec/IEPPV>

3.3 Other Normative References

- Department of Defense Architecture Framework (DoDAF), Version 2.02, August 2010, <http://dodcio.defense.gov/Library/DoDArchitectureFramework.aspx>
- DM2 - DoDAF Meta-Model,
- The DM2 Conceptual Data Model, http://dodcio.defense.gov/Library/DoDArchitectureFramework/dodaf20_conceptual.aspx
- DM2 Logical Data Model, http://dodcio.defense.gov/Library/DoDArchitectureFramework/dodaf20_logical.aspx
- DM2 Formal Ontology. http://dodcio.defense.gov/Library/DoDArchitectureFramework/dodaf20_ontology1.aspx
- Department National Defence and Canadian Forces (DND/ CF) Architecture Framework (DNDAF), Version 1.8.1, 25 January 2013
- International Defence Enterprise Architecture Specification for Exchange (IDEAS) Group, <http://www.ideasgroup.org/>
- IDEAS Foundation, <http://www.ideasgroup.org/foundation/>
- IDEAS Foundation v1.0 as XMI File (zipped), <http://www.ideasgroup.org/7Documents/>
- ISO/IEC/IEEE 42010:2011, Systems and software engineering – Architecture Description, http://www.iso.org/iso/catalogue_detail.htm?csnumber=50508
- Ministry of Defence Architecture Framework (MODAF), <https://www.gov.uk/mod-architecture-framework>
- MODAF Ontological Data Exchange Mechanism (MODEM)
- https://www.gov.uk/government/uploads/system/uploads/attachment_data/file/63980/20130117_MODAF_MODEM.pdf
- NATO Architecture Framework (NAF),

- Version 3, NATO C3 BOARD (AC/322-D(2007)0048), <http://www.nhq3s.nato.int/HomePage.asp> (no longer publicly available online as of 3 November 2015)
- NATO Architecture Framework v4.0 Documentation.

3.4 Informative References

- Business Process Model & Notation (BPMN), Version 2.0.2, January 2014 <https://www.omg.org/spec/BPMN>
- ISO 15704:2000, Industrial Automation Systems – “Requirements for Enterprise-Reference Architectures and Methodologies,” http://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=28777
- ISO 8601:2004 Data elements and interchange formats – Information interchange – Representation of dates and times, http://www.iso.org/iso/home/store/catalogue_ics/catalogue_detail_ics.htm?ics1=01&ics2=140&ics3=30&csnumber=40874
- ISO/IEC 15288:2015, "Systems Engineering - Systems Life Cycle Processes," http://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=63711
- Object Management Group (OMG), Metamodel Extension Facility, Initial submission, ad/12-02-01, <https://www.omg.org/cgi-bin/doc?ad/12-02-01> (Requires OMG Member Access)
- OASIS SOA-RAF, Reference Architecture Foundation for Service Oriented Architecture Version 1.0, OASIS SOA Reference Model TC, 04 December 2012. <http://docs.oasis-open.org/soa-rm/soa-ra/v1.0/cs01/soa-ra-v1.0-cs01.pdf> (Authoritative)
- Object Management Group (OMG), Semantics of Business Vocabulary and Business Rules (SBVR), Version 1.3, May 2015, <https://www.omg.org/spec/SBVR>
- Business Motivation Model (BMM), Version 1.3, <http://www.omg.org/spec/BMM/1.3/>
- International Council On Systems Engineering (INCOSE), Systems Engineering Handbook V4, 2015, <http://www.incose.org/ProductsPublications/sehandbook>

4 Terms and Definitions

No new terms and definitions have been required to create this specification. All terms are available in the normative references or bibliographic citations for detailed explanation.

5 Symbols

For the purposes of this specification, the following List of symbols/abbreviations apply.

Table 5:1 - Description of acronyms used in this specification

AcV-* ²	Acquisition View
AD	Architecture Description
AV-*	All View
BMM	Business Motivation Model
BPMN	Business Process Modeling Notation
C4ISR	Command, Control, Communications, Computers, Intelligence, Surveillance, and Reconnaissance
CaT	Capability Team
COI	Communities of Interest
CV-*	Capability View
DIV-*	Data and Information Views
DLOD	Defence Lines of Development
DM2	DoDAF Meta Model
DMM	Domain Meta Model
DNDAF	Department National Defence and Canadian Forces (DND/ CF) Architecture Framework
DoD	United States Department of Defense
DoDAF	Department of Defense Architecture Framework
DOTMLP	Doctrine, Organization, Training, Material, Leadership, Personnel, Facilities
EIE	Enterprise Information Environment
IDEAS	International Defense Enterprise Architecture Specification for Exchange
IDEF	Integrated DEFinition Methods
INCOSE	International Council Of Systems Engineering
JCIDS	Joint Capabilities Integration and Development System
MISIG	Model Interchange Special Interest Group
MOD	United Kingdom Ministry of Defence
MODAF	Ministry of Defence Architecture Framework
MODEM	MODAF Ontological Data Exchange Mechanism
NAF	NATO Architecture Framework
OASIS	Organization for the Advancement of Structured Information Standards
OSLC	Open Services for Lifecycle Collaboration
OV-*	Operational View
PES	DoDAF Physical Exchange Specification
POC	Proof of Concept
PV-*	Project View
RDF	Resource Description Framework
SoaML	Service orientated architecture Modeling Language
SoS	System of Systems

² * denotes a wildcard

SOV-*	Service Oriented View
StdV-*	Standards View in DoDAF 2.02 compare TV-* in UAF
STV-*	Strategic View
SV-*	System View
SvcV-*	Service View
TEPID OIL	Training, Equipment, Personnel, Information, Concepts and Doctrine, Organisation, Infrastructure, Logistics
TOGAF	The Open Group Architectural Framework©
TPPU	Task, Post, Process, and Use
TV-*	Technical View
UAF	Unified Architecture Framework
UAFP	Unified Architecture Framework Profile
UPDM	Unified Profile for DoDAF/MODAF

6 Additional Information

6.1 Changes to Adopted OMG Specifications

This specification completely replaces Unified Architecture Framework (UAF), version 1.0
<https://www.omg.org/spec/UAF/About-UAF/>

6.2 Language Architecture

The UAF specification reuses a subset of UML 2.5.1 and SysML 1.5 and provides additional extensions needed to address requirements in the UPDM 3.0 RFP Mandatory Requirements. Those requirements form the basis for this specification. This specification documents the language architecture in terms of UML 2.5.1 and SysML 1.5 and specifies how to implement UAF. This clause explains design principles and how they are applied to define the UAF language architecture.

6.3 Philosophy

The UAF development uses a model-driven approach. A simple description of the work process is:

- A Domain Metamodel (DMM) uses UML Class models to represent individuals, types and tuples that aggregate the concepts defined in DoDAF, MODEM, NAF, DNDAF and other frameworks.
- The aligned and renamed viewpoints from the various frameworks provide a common generic name for each viewpoint. It should be noted that the term viewpoint is in the context of ISO 42010 where a viewpoint is the specification of a view. The UAF viewpoints are mapped to the corresponding viewpoint in the relevant contributing framework. It is the viewpoints described in the DMM that provides the basis for the Unified Architecture Framework (UAF).
- The UAF provides an abstraction layer that separates the underlying UAF metamodel from the presentation layer. The results of this mapping are given in Appendix A (see document dtc/19-06-17 and an overview of the viewpoints in a grid format are given in this document).
- The intent of the UAF is to provide a Domain MetaModel usable by non-UML/SysML tool vendors who may wish to implement the UAF within their own tool and metalanguage.
- The Unified Architecture Framework Profile (UAFP) is the standard implementation of the UAF DMM. It was created by mapping the UAF concepts and relationships to corresponding stereotypes in the UAFP.
- The UAFP analysis and refactoring reflects language architecture, tool implementation, and reuse considerations.
- The specification is generated from the UML model used to describe the UAF DMM and UAFP. This approach allows the team to concentrate on architecture issues rather than documentation production. The UML tool automatically maintains consistency. The UML tool improves maintenance and enables traceability between the UAF and the UAFP where every stereotype is linkable to the UAF element using UML Abstraction relationship.

6.4 Core Principles

The fundamental design principles for UAF DMM are:

- **Requirements-driven:** UAF is intended to satisfy the requirements of the UPDM 3.0 RFP Mandatory Requirements.
- **Influence from donor Frameworks:** The DMM was based upon an aggregation of concepts and relationships from the donor frameworks.
- **IDEAS Ontology driven:** The DMM was based upon a simplified version of the IDEAS ontology, see chapter 8.

- **DMM Notation:** The DMM was expressed using UML class diagram notation.
- **Reusability of UML Metamodel concepts:** The UAF DMM reuses a number of concepts from the UML Metamodel, such as Statemachines, Activities and Interactions. The explicit relationship to these concepts enables the UAF DMM to reuse UML semantics instead of reinventing its own semantics.
- **Reusability of BPMN concepts:** The UAF DMM reuses a number of concepts from BPMN, such as processes. The explicit relationship to these concepts enables the UAF DMM to reuse BPMN semantics instead of reinventing its own semantics.

7 UAF Grid

Due to the complexity of managing the multiple viewpoints with overlapping concerns and metamodels, the standard viewpoints are refactored as described in the donor frameworks into a more manageable format. This decision led to the development of the UAF grid which is described below.

The grid is a way of showing how the various viewpoints (known as *view specifications* in the rest of document) correspond to *domains* (horizontal rows) and the *model kinds* (the columns) that describe the view specification. The intent of the grid is not to be complete, but to capture the information that is present in the frameworks that contributes to the UAF, consequently, some gaps are evident.

	Taxonomy Tx	Structure Sr	Connectivity Cn	Processes Pr	States St	Interaction Scenarios Is	Information ^c If	Parameters ^d Pm	Constraints Ct	Roadmap Rm	Traceability Tr
Metadata^a Md	Metadata Taxonomy Md-Tx ^f	Metadata Structure Md-Sr	Metadata Connectivity Md-Cn	Metadata Processes Md-Pr	Metadata States Md-St	-	Conceptual Data Model,	Environment Pm-En	Metadata Constraints Md-Ct	Metadata Roadmap Md-Rm	Metadata Traceability Md-Tr
Strategic St	Strategic Taxonomy St-Tx	Strategic Structure St-Sr	Strategic Connectivity St-Cn	-	Strategic States St-St	-			Strategic Constraints St-Ct	Strategic Deployment, St-Rm, Strategic Phasing St-Rm	Strategic Traceability St-Tr
Operational Op	Operational Taxonomy Op-Tx	Operational Structure Op-Sr	Operational Connectivity Op-Cn	Operational Processes Op-Pr	Operational States Op-St	Operational Interaction Scenarios Op-Is			Operational Constraints Op-Ct	-	Operational Traceability Op-Tr
Services Sv	Service Taxonomy Sv-Tx	Service Structure Sv-Sr	Service Connectivity Sv-Cn	Service Processes Sv-Pr	Service States Sv-St	Service Interaction Scenarios Sv-Is			Service Constraints Sv-Ct	Service Roadmap Sv-Rm	Service Traceability Sv-Tr
Personnel Pr	Personnel Taxonomy Pr-Tx	Personnel Structure Pr-Sr	Personnel Connectivity Pr-Cn	Personnel Processes Pr-Pr	Personnel States Pr-St	Personnel Interaction Scenarios Pr-Is	Logical Data Model,	Measurements Pm-Me	Competence, Drivers, Performance Pr-Ct	Personnel Availability, Personnel Evolution, Personnel Forecast Pr-Rm	Personnel Traceability Pr-Tr
Resources Rs	Resource Taxonomy Rs-Tx	Resource Structure Rs-Sr	Resource Connectivity Rs-Cn	Resource Processes Rs-Pr	Resource States Rs-St	Resource Interaction Scenarios Rs-Is	Physical schema ^e , real world results		Resource Constraints Rs-Ct	Resource evolution, Resource forecast Rs-Rm	Resource Traceability Rs-Tr
Security Sc	Security Taxonomy Sc-Tx	Security Structure Sc-Sr	Security Connectivity Sc-Cn	Security Processes Sc-Pr	-	-	Security Constraints Sc-Ct		-	Security Traceability Sc-Tr	
Projects Pj	Project Taxonomy Pj-Tx	Project Structure Pj-Sr	Project Connectivity Pj-Cn	Project Processes Pj-Pr	-	-	-		Project Roadmap Pj-Rm	Project Traceability Pj-Tr	
Standards Sd	Standard Taxonomy Sd-Tx	Standards Structure Sd-Sr	-	-	-	-	-	-	Standards Roadmap Sd-Rm	Standards Traceability Sd-Tr	
Actual Resources Ar		Actual Resources Structure Ar-Sr	Actual Resources Connectivity Ar-Cn	Simulation ^b				Parametric Execution/ ^b Evaluation	-	-	
Dictionary Dc											
Summary & Overview Sm-Ov											
Requirements Req											

Figure 7:1- UAF Grid

Notes related to suffixes in the grid:

- The view specifications in the Metadata Domain are not modeled as part of the UAF but are architectural artifacts that contribute to the success in defining and developing an architecture.
- To be able to evaluate architecture behavior and constraints (i.e., non-functional requirements) it is necessary to define actual instances of the architectural elements. The expectation is that tool vendors intending to implement the UAF have capabilities native to their tools to enable behavioral simulation and the evaluation of measures and constraints through parametric diagrams or a proprietary equivalent.
- The information model is a column across the domains and can be defined in any of its forms, i.e., Conceptual, Logical or Physical. The expectation is that most developers of the information model will use the Conceptual or Logical forms of the data model when using an abstract modeling tool.

- d. The parameters column captures the measures and environments across the architecture in all the different domains.
- e. The expectation is that the physical schema model would not be defined in the UAF. Any tool implementing the framework provides a means to import or link-to representations of the physical model.
- f. The Metadata Taxonomy view specification provides a means to extend the framework to other domains.

The detailed mapping between the view specifications of the UAF shown in the grid and the viewpoints from the donor frameworks is described in dtc\2019-06-17. A definition for each view specification in the grid is described in the following chapters.

7.1 Descriptions of Domains and Model Kinds

Table 7:1 - Definitions for the Domains

Domain	Acronym	Description
Metadata	Md	Identifies the metadata required to develop a suitable architecture that is fit for its purpose.
Strategic	St	Capability management process. Describes the capability taxonomy, composition, dependencies and evolution.
Operational	Op	Illustrates the Logical Architecture of the enterprise. Describes the requirements, operational behavior, structure, and exchanges required to support (exhibit) capabilities. Defines all operational elements in an implementation/solution independent manner.
Services	Sv	The Service-Orientated View (SOV) is a description of services needed to directly support the operational domain as described in the Operational View. A service within MODAF is understood in its broadest sense, as a unit of work through which a provider provides a useful result to a consumer. DoDAF: The Service Views within the Services Viewpoint describe the design for service-based solutions to support operational development processes (JCIDS) and Defense Acquisition System or capability development within the Joint Capability Areas.
Personnel	Pr	Defines and explores organizational resource types. Shows the taxonomy of types of organizational resources as well as connections, interaction and growth over time.
Resources	Rs	Captures a solution architecture consisting of resources, e.g., organizational, software, artifacts, capability configurations, and natural resources that implement the operational requirements. Further design of a resource is typically detailed in SysML or UML.
Security	Sc	Security assets and security enclaves. Defines the hierarchy of security assets and asset owners, security constraints (policy, laws, and guidance) and details where they are located (security enclaves).
Projects	Pj	Describes projects and project milestones, how those projects deliver capabilities, the organizations contributing to the projects and dependencies between projects.
Standards	Sd	MODAF: Technical Standards Views are extended from the core DoDAF views to include non-technical standards such as operational doctrine, industry process standards, etc. DoDAF: The Standards Views within the Standards Viewpoint are the set of rules governing the arrangement, interaction, and interdependence of solution parts or elements.
Actual Resources	Ar	The analysis, e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations. Illustrates the expected or achieved actual resource configurations.

Table 7:2 - Definitions of the Model Kinds

Model Kind	Acronym	Description
Taxonomy	Tx	Presents all the elements as a standalone structure. Presents all the elements as a specialization hierarchy, provides a text definition for each one and references the source of the element
Structure	Sr	Describes the definitions of the dependencies, connections, and relationships between the different elements.
Connectivity	Cn	Describes the connections, relationships, and interactions between the different elements.
Processes	Pr	Captures activity based behavior and flows. It describes activities, their Inputs/Outputs, activity actions and flows between them.
States	St	Captures state-based behavior of an element. It is a graphical representation of states of a structural element and how it responds to various events and actions.
Interaction Scenarios	Is	Expresses a time ordered examination of the exchanges as a result of a particular scenario. Provides a time-ordered examination of the exchanges between participating elements as a result of a particular scenario.
Information	If	Address the information perspective on operational, service, and resource architectures. Allows analysis of an architecture's information and data definition aspect, without consideration of implementation specific issues.
Constraints	Ct	Details the measurements that set performance requirements constraining capabilities. Also defines the rules governing behavior and structure.
Roadmap	Rm	Addresses how elements in the architecture change over time. Also, how at different points in time or different periods of time.
Traceability	Tr	Describes the mapping between elements in the architecture. This can be between different viewpoints within domains as well as between domains. It can also be between structure and behaviors.

7.2 Domain Interrelationships

Although the grid is the primary means of expressing the relationship between the Domains, Model Kinds and View Specifications, because of its two-dimensional nature it is not adequate to explain the abstract interrelationships that exist between the domains. The following diagram is an indication of how the domains are interrelated.




Figure 7:2 - Domain Interrelationships

Where a Domain is shown vertically the intent is to show that the Domain is a cross cutting concern that goes across the levels of abstraction in the architecture.

Where a Domain is shown horizontally the intent is to show that the Domain exists in a layer of abstraction between the Domains above and below it and there is an interrelationship with the Domains either side of it.

7.3 Domain Metamodel Diagram Legend

This Annex comprises of various diagrams that document the Domain Metamodel (DMM) that document the MoDAF 1.5 and MoDAF 1.2 integrated model. This model was used as a basis for creating the UPDM profile.

Note that the diagrams rely on color to aid the reader in understanding the model. Please refer to the legend below to understand the diagrams.

The following is the legend of element colors used in the DMM and what they denote.




Figure 7:3 - Legend of color codes for element types defined in UAF

The meaning of the element types in the UAF are based upon concepts put forth in the International Defence Enterprise Architecture Specification (IDEAS).

- An Individual denotes a single instance of an element.
- A Type denotes a set of Individuals.
- A Tuple denotes a relationship that exists between elements.
- An Abstract denotes that the element has no direct use but is a means of construction.
- An Enumeration is a complete, ordered listing of all the items in a collection.
- An External Type is an element that exists outside of the core DMM but is referenceable by elements in the DMM.

8 Domain Metamodel Diagrams

Note that the diagrams rely on color to aid the reader in understanding the model. Please refer to the legend in the various diagrams to understand the specific definitions.

8.1 View Specifications

This section documents each of the view specifications of UAF.

8.1.1 View Specifications::Metadata

Stakeholders: Enterprise Architects, Technical Managers.

Concerns: architecture development process, architecture traceability, metamodel and its extensions, architecture versioning.

Definition: Identifies the metadata required to develop a suitable architecture that is fit for its purpose.

View Specifications::Metadata::Taxonomy

Stakeholders: Enterprise Architects, Technical Managers.

Concerns: metamodel and its extensions.

Definition: captures user defined metamodel extensions

Recommended Implementation: UML Profile Diagram, SysML Block Definition Diagram

View Specifications::Metadata::Structure

Stakeholders: Enterprise Architects, Technical Managers.

Concerns: domains, model kinds, and view specifications that are used to describe the architecture.

Definition: (i) lists predefined and custom domains, model kinds, and view specifications (ii) and identify the key stakeholders and their concerns.

Recommended Implementation: SysML Block Definition Diagram, SysML Package Diagram.

View Specifications::Metadata::Connectivity

Stakeholders: Enterprise Architects, people who want to understand relationships to related architectural descriptions, Technical Managers.

Concerns: high-level dependencies between architectural descriptions.

Definition: depicts and analyzes all relevant dependencies between architectural descriptions, e.g., reference architectures, as-is to to-be architectures.

Recommended Implementation: SysML Block Definition Diagram, SysML Package Diagram, matrix format.

View Specifications::Metadata::Processes

Stakeholders: Enterprise Architects, people who want to understand the architecture development process, Technical Managers.

Concerns: methodology used.

Definition: methodology used in developing the architecture.

Recommended Implementation: SysML Activity Diagram, text.

View Specifications::Metadata::States

Stakeholders: Enterprise Architects, people who want to understand the architecture governance, Technical Managers.

Concerns: architecture status.

Definition: captures version number and approval workflow of the architecture.

Recommended Implementation: SysML State Machine Diagram, state table, text.

View Specifications::Metadata::Constraints

Stakeholders: Enterprise Architects, people who want to understand constraints for the architecture, Technical Managers.

Concerns: architectural constraints.

Definition: captures assumptions and constraints on the architecture.

Recommended Implementation: tabular format, text.

View Specifications::Metadata::Roadmap

Stakeholders: Enterprise Architects, people who want to understand the architecture development plan, Technical Managers.

Concerns: architecture release schedule.

Definition: captures project timeline for the architecture.

Recommended Implementation: timeline, text.

View Specifications::Metadata::Traceability

Stakeholders: Enterprise Architects, people who want to understand impact of change across the architecture supporting assets, Technical Managers.

Concerns: reuse of architectures.

Definition: shows references to asset libraries, legacy architectures, and external sources, e.g., documents.

Recommended Implementation: SysML Block Definition Diagram, SysML Package Diagram, tabular format.

8.1.2 View Specifications::Strategic

Stakeholders: Capability Portfolio Managers.

Concerns: capability management process.

Definition: describe capability taxonomy, composition, dependencies and evolution.

View Specifications::Strategic::Taxonomy

Contains the diagrams that document the Strategic Taxonomy Viewpoint.

View Specifications::Strategic::Taxonomy::Strategic Taxonomy

Stakeholders: PMs, Enterprise Architects, Executives.

Concerns: capability needs.

Definition: shows the taxonomy of capabilities.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:1 - Strategic Taxonomy Elements

- [Capability](#)
- [CapabilityGeneralization](#)
- [CapabilityRole](#)

View Specifications::Strategic::Structure

Contains the diagrams that document the Strategic Structure Viewpoint.

View Specifications::Strategic::Structure::Strategic Structure

Stakeholders: PMs, Enterprise Architects, Executives.

Concerns: capability needs.

Definition: shows the relationship between EnterprisePhases and the Capabilities that are intended to be developed during the enterprise phases, and the organizations involved in the enterprise.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:2 - Strategic Structure

Elements

- [ActualEnduringTask](#)
- [ActualEnterprisePhase](#)
- [ActualOrganization](#)
- [ActualResponsibleResource](#)
- [Capability](#)
- [CapableElement](#)
- [EnduringTask](#)
- [EnterpriseGoal](#)
- [EnterprisePhase](#)
- [EnterpriseVision](#)
- [Exhibits](#)
- [OperationalArchitecture](#)
- [OrganizationInEnterprise](#)
- [ResourceArchitecture](#)
- [StructuralPart](#)
- [TemporalPart](#)
- [WholeLifeEnterprise](#)

View Specifications::Strategic::Connectivity

Contains the diagrams that document the Strategic Connectivity Viewpoint.

View Specifications::Strategic::Connectivity::Strategic Connectivity

Stakeholders: PMs, Executives, Enterprise Architects.

Concerns: capability dependencies.

Definition: describes the dependencies between planned capabilities.

Recommended Implementation: SysML Block Definition Diagram. SysML Internal Block Diagram.




Figure 8:3 - Strategic Connectivity

Elements

- [Capability](#)
- [CapabilityDependency](#)
- [CapabilityRole](#)
- [CapabilityRoleDependency](#)

View Specifications::Strategic::States

Contains the diagrams that document the Strategic States Viewpoint.

View Specifications::Strategic::States::Strategic States

Stakeholders: PMs, Enterprise Architects.

Concerns: effects that the implementation(s) of capabilities are expected to deliver.

Definition: captures the relationships between capability(ies) and desired effect(s) that implementation(s) of capability(ies) should achieve.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:4 - Strategic States

Elements

- [AchievedEffect](#)
- [Achiever](#)
- [ActualOrganization](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualResource](#)
- [ActualResponsibleResource](#)
- [ActualState](#)
- [Capability](#)
- [CapabilityConfiguration](#)
- [DesiredEffect](#)
- [Desirer](#)
- [FieldedCapability](#)
- [NaturalResource](#)
- [OperationalAgent](#)
- [OperationalPerformer](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourceArchitecture](#)

- [ResourceArtifact](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [Software](#)
- [Technology](#)

View Specifications::Strategic::Constraints

Contains the diagrams that document the Strategic Constraints Viewpoint.

View Specifications::Strategic::Constraints::Strategic Constraints

Stakeholders: PMs, Enterprise Architects.

Concerns: capability constraints.

Definition: details the measurements that set performance requirements constraining capabilities.

Recommended Implementation: tabular format, SysML Block Definition Diagram.




Figure 8:5 - Strategic Constraints

Elements

- [Capability](#)
- [Measurement](#)
- [PropertySet](#)

View Specifications::Strategic::Roadmap

Contains the diagrams that document the Strategic Roadmap Viewpoint.

View Specifications::Strategic::Roadmap::Deployment

View Specifications::Strategic::Roadmap::Deployment::Strategic Roadmap: Deployment

Stakeholders: PMs, Executives, Enterprise Architects.

Concerns: capability deployment to organizations over time.

Definition: addresses the deployment of capability(ies) to actual organizations over time.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:8 - Strategic Traceability

Elements

- [ActualEnduringTask](#)
- [Capability](#)
- [CapabilityForTask](#)
- [Function](#)
- [Implements](#)
- [MapsToCapability](#)
- [OperationalActivity](#)
- [Process](#)
- [StandardOperationalActivity](#)

8.1.3 View Specifications::Operational

Stakeholders: Business Architects, Executives.

Concerns: illustrate the Logical Architecture of the enterprise.

Definition: describe the requirements, operational behavior, structure, and exchanges required to support (exhibit) capabilities. Defines all operational elements in an implementation/solution independent manner.

View Specifications::Operational::Taxonomy

Contains the diagrams that document the Operational Taxonomy Viewpoint.

View Specifications::Operational::Taxonomy::Operational Taxonomy

Stakeholders: Business Architects, Systems Engineers, Enterprise Architects, Owners responsible for Operational Agents.

Concerns: OperationalAgent types.

Definition: shows the taxonomy of types of OperationalAgents.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:9 - Operational Taxonomy

Elements

- [ArbitraryConnector](#)
- [Asset](#)
- [CapabilityConfiguration](#)
- [ConceptItem](#)
- [HighLevelOperationalConcept](#)
- [Location](#)
- [NaturalResource](#)
- [OperationalAgent](#)
- [OperationalAsset](#)
- [OperationalPerformer](#)
- [Organization](#)
- [OrganizationalResource](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceAsset](#)
- [ResourcePerformer](#)
- [Software](#)

View Specifications::Operational::Structure

Contains the diagrams that document the Operational Structure Viewpoint.

View Specifications::Operational::Structure::Operational Structure

Stakeholders: Business Architects, Systems Engineers, Enterprise Architects, Owners responsible for Operational Agents.

Concerns: identifies the operational exchange requirements between nodes.

Definition: defines operational architecture and exchange requirements necessary to support a specific set of Capability(ies).

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:10 - Operational Structure

Elements

- [ActualEnvironment](#)
- [ActualLocation](#)
- [Asset](#)
- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)
- [IsCapableToPerform](#)
- [KnownResource](#)
- [LocationHolder](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [OperationalArchitecture](#)
- [OperationalAsset](#)
- [OperationalPerformer](#)
- [OperationalRole](#)
- [ProblemDomain](#)

View Specifications::Operational::Connectivity

Contains the diagrams that document the Operational Connectivity Viewpoint.

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [ActualMeasurementSet](#)
- [ActualService](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [OperationalActivity](#)
- [OperationalActivityAction](#)
- [OperationalActivityEdge](#)
- [OperationalAgent](#)
- [OperationalExchange](#)
- [OperationalExchangeItem](#)
- [OperationalMethod](#)
- [OperationalParameter](#)
- [OperationalPerformer](#)
- [OperationalRole](#)
- [PerformsInContext](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [RequiredServiceLevel](#)
- [ServiceSpecification](#)
- [StandardOperationalActivity](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Operation
- UML2.5Metamodel::Parameter

View Specifications::Operational::Processes::Operational Processes BPMN Semantics

Stakeholders: Business Architect, Enterprise Architects.

Concerns: captures activity based behavior and flows using BPMN notation.

Definition: describes the BPMN processes that are normally conducted in the course of achieving business goals that support a capability. It describes operational activities, their Inputs/Outputs, operational activity actions and flows between them using BPMN notation.

Recommended Implementation: BPMN Process Diagram.




Figure 8:13 - Operational Processes BPMN Semantics

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [ActualEnduringTask](#)
- [ActualMeasurementSet](#)
- [ActualService](#)
- [AssetRole](#)
- BPMN2Metamodel::BPMNMessage
- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::MessageFlow
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [EnduringTask](#)
- [Exchange](#)
- [ExchangeItem](#)
- [Implements](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [OperationalActivity](#)
- [OperationalActivityAction](#)
- [OperationalActivityEdge](#)

- [OperationalAgent](#)
- [OperationalExchange](#)
- [OperationalExchangeItem](#)
- [OperationalMethod](#)
- [OperationalParameter](#)
- [OperationalPerformer](#)
- [OperationalRole](#)
- [PerformsInContext](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessUsage](#)
- [RequiredServiceLevel](#)
- [ServiceSpecification](#)
- [StandardOperationalActivity](#)

View Specifications::Operational::States

Contains the diagrams that document the Operational States Viewpoint.

View Specifications::Operational::States::Operational States

Stakeholders: Systems Engineers, Software Engineers.

Concerns: capture state-based behavior of an operational OperationalPerformer.

Definition: it is a graphical representation of states of an operational OperationalPerformer and how that operational OperationalPerformer responds to various events and actions.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:14 - Operational States

Elements

- [OperationalAgent](#)
- [OperationalStateDescription](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Operational::Interaction Scenarios

Contains the diagrams that document the Operational Interaction Scenarios Viewpoint.

View Specifications::Operational::Interaction Scenarios::Operational Interaction Scenarios

Stakeholders: Systems Engineers, Business Architects.

Concerns: express a time ordered examination of the operational exchanges as a result of a particular operational scenario.

Definition: provides a time-ordered examination of the operational exchanges between participating nodes (OperationalPerformer roles) as a result of a particular operational scenario.

Recommended Implementation: SysML Sequence Diagram, BPMN Collaboration Diagram.




Figure 8:15 - Operational Interaction Scenarios

Elements

- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [OperationalExchange](#)
- [OperationalInteractionScenario](#)
- [OperationalMessage](#)
- [OperationalMethod](#)
- [OperationalPerformer](#)
- [OperationalRole](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Operational::Constraints

Contains the diagrams that document the Operational Constraints Viewpoint.

View Specifications::Operational::Constraints::Operational Constraints

Stakeholders: Systems Engineers, Architects, Program Sponsors

Concerns: define operational limitations, constraints and performance parameters for the enterprise.

Definition: specifies traditional textual operational or business rules that are constraints on the way that business is done in the enterprise. The addition of SysML parametrics provides a computational means of defining operational constraints across the enterprise or within a specific operational context.

Recommended Implementation: tabular format, SysML Block Definition Diagram, SysML Parametric Diagram.




Figure 8:16 - Operational Constraints

Elements

- [DataModel](#)
- [InformationElement](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [OperationalConstraint](#)
- [OperationalExchange](#)
- [OperationalPerformer](#)
- [Rule](#)
- [SubjectOfOperationalConstraint](#)

View Specifications::Operational::Traceability

Contains the diagrams that document the Operational Traceability Viewpoint.

View Specifications::Operational::Traceability::Operational Traceability

Stakeholders: PMs, Enterprise Architects, Business Architects.

Concerns: traceability between capabilities and operational activities and capabilities and operational agents.

Definition: describes the mapping between the capabilities required by an Enterprise and the supporting operational

activities and operational agents.

Recommended Implementation: matrix format, SysML Block Definition Diagram.




Figure 8:17 - Operational Traceability

Elements

- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)
- [MapsToCapability](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [OperationalArchitecture](#)
- [OperationalPerformer](#)
- [Process](#)

8.1.4 View Specifications::Services

Stakeholders: Enterprise Architects, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: specifications of services required to exhibit a Capability.

Definition: shows Service Specifications and required and provided service levels of these specifications required to exhibit a Capability or to support an Operational Activity.

View Specifications::Services::Taxonomy

Contains the diagrams that document the Services Taxonomy Viewpoint.

View Specifications::Services::Taxonomy::Services Taxonomy

Stakeholders: Enterprise Architects, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: service specification types and required and provided service levels of these types.

Definition: shows the taxonomy of types of services and the level of service that they are expected to provide or are required to meet through the display of ActualMeasurements associated with the Provided and Required Service Level.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:18 - Services Taxonomy

Elements

- [ActualMeasurement](#)
- [ActualMeasurementSet](#)
- [ActualService](#)
- [Measurement](#)
- [PropertySet](#)
- [ProvidedServiceLevel](#)
- [RequiredServiceLevel](#)
- [ServicePolicy](#)
- [ServiceSpecification](#)
- [ServiceSpecificationGeneralization](#)

View Specifications::Services::Structure

Contains the diagrams that document the Services Structure Viewpoint.

View Specifications::Services::Structure::Services Structure

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: combination of services required to exhibit a capability.

Definition: shows the composition of services and how services are combined into a higher level service required to exhibit a capability or support an operational activity.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:19 - Services Structure

Elements

- [InformationElement](#)
- [Measurement](#)
- [OperationalExchangeItem](#)
- [PropertySet](#)
- [ServiceConnector](#)
- [ServiceInterface](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServicePort](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)

View Specifications::Services::Connectivity

Contains the diagrams that document the Services Connectivity Viewpoint.

View Specifications::Services::Connectivity::Services Connectivity

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: interoperability among services

Definition: specifies service interfaces, e.g., provided and required service operations, to ensure compatibility and reusability of services.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram, tabular format.




Figure 8:20 - Services Connectivity

Elements

- [ServiceConnector](#)
- [ServiceInterface](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServicePort](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)

View Specifications::Services::Processes

Contains the diagrams that document the Services Processes Viewpoint.

View Specifications::Services::Processes::Services Processes

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: the behavior of a service in terms of the operational activities it is expected to support.

Definition: provides detailed information regarding the allocation of service functions to service specifications, and data flows between service functions.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram.




Figure 8:21 - Services Processes

Elements

- [IsCapableToPerform](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [ServiceFunction](#)
- [ServiceFunctionAction](#)
- [ServiceFunctionEdge](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServiceSpecification](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Operation
- UML2.5Metamodel::Parameter

View Specifications::Services::Processes::Services Processes BPMN Semantics

Stakeholders: Solution Providers, Software Architects, Business Architects.

Concerns: the behavior of a service in terms of the operational activities it is expected to support.

Definition: provides detailed information regarding the allocation of service functions to service specifications, and data flows between service functions using BPMN.

Recommended Implementation: BPMN Process Diagram, SysML Block Definition Diagram.




Figure 8:22 - Services Processes BPMN Semantics

Elements

- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [InteractionRole](#)
- [IsCapableToPerform](#)
- [PerformsInContext](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessUsage](#)
- [ServiceFunction](#)
- [ServiceFunctionAction](#)
- [ServiceFunctionEdge](#)
- [ServiceMethod](#)
- [ServiceParameter](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)

View Specifications::Services::States

Contains the diagrams that document the Services States Viewpoint.

View Specifications::Services::States::Services States

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: the behavior of a service specification in terms of states and events causing transitions between states.

Definition: specifies the possible states a service specification may have, and the possible transitions between those states.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:23 - Services States

Elements

- [ServiceSpecification](#)
- [ServiceStateDescription](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Services::Interaction Scenarios

Contains the diagrams that document the Services Interaction Scenarios Viewpoint.

View Specifications::Services::Interaction Scenarios::Services Interaction Scenarios

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: the behavior of a service specification in terms of expected time-ordered examination of the interactions between service roles.

Definition: specifies how a service roles interact with each other, service providers and consumers, and the sequence and dependencies of those interactions.

Recommended Implementation: SysML Sequence Diagram.




Figure 8:24 - Services Interaction Scenarios

Elements

- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [ServiceFunction](#)
- [ServiceInteractionScenario](#)
- [ServiceMessage](#)
- [ServiceMethod](#)
- [ServiceSpecification](#)
- [ServiceSpecificationRole](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Services::Constraints

Contains the diagrams that document the Services Constraints Viewpoint.

View Specifications::Services::Constraints::Services Constraints

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: service policies that apply to implementations of service specifications.

Definition: specifies traditional textual service policies that are constraints on the way that service specifications are implemented within resources. The addition of SysML parametrics provide a computational means of defining service policies across the enterprise or within a specific service configuration.

Recommended Implementation: tabular format, SysML Parametric Diagram.



Figure 8:25 - Services Constraints

Elements

- [Rule](#)
- [ServicePolicy](#)
- [ServiceSpecification](#)

View Specifications::Services::Roadmap

Contains the diagrams that document the Services Roadmap Viewpoint.

View Specifications::Services::Roadmap::Services Roadmap

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: service specification changes over time.

Definition: provides an overview of how a service specification changes over time. It shows the combination of several service specifications mapped against a timeline.

Recommended Implementation: timeline, SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:26 - Services Roadmap

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [ServiceSpecification](#)

- [VersionedElement](#)
- [VersionOfConfiguration](#)
- [VersionSuccession](#)
- [WholeLifeConfiguration](#)

View Specifications::Services::Traceability

Contains the diagrams that document the Services Traceability Viewpoint.

View Specifications::Services::Traceability::Services Traceability

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: traceability between operational activities and service specifications that support them.

Definition: depicts the mapping of service specifications to operational activities and how service specifications contribute to the achievement of a capability.

Recommended Implementation: tabular or matrix format.




Figure 8:27 - Services Traceability

Elements

- [ActualService](#)
- [Capability](#)
- [CapableElement](#)
- [Consumes](#)
- [Exhibits](#)
- [OperationalActivity](#)
- [ServiceSpecification](#)

8.1.5 View Specifications::Personnel

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: human factors.

Definition: aims to clarify the role of Human Factors (HF) when creating architectures in order to facilitate both Human Factors Integration (HFI) and systems engineering (SE).

View Specifications::Personnel::Taxonomy

Contains the diagrams that document the Personnel Taxonomy Viewpoint.

View Specifications::Personnel::Taxonomy::Personnel Taxonomy

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: organizational resource types.

Definition: shows the taxonomy of types of organizational resources.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:28 - Personnel Taxonomy

Elements

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)

View Specifications::Personnel::Structure

Contains the diagrams that document the Personnel Structure Viewpoint.

View Specifications::Personnel::Structure::Personnel Structure

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: typical organizational structure used to support a capability(ies).

Definition: shows organizational structures and possible interactions between organizational resources.

Recommended Implementation: SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:29 - Personnel Structure

Elements

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [PostRole](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- [SubOrganization](#)

View Specifications::Personnel::Connectivity

Contains the diagrams that document the Personnel Connectivity Viewpoint.

View Specifications::Personnel::Connectivity::Personnel Connectivity

Stakeholders: Solution providers.

Concerns: interaction of organizational resources.

Definition: captures the possible interactions between organizational resources, including command and control relationships. Interactions typically illustrate the fundamental roles and management responsibilities.

Recommended Implementation: tabular format.




Figure 8:30 - Personnel Connectivity

Elements

- [Command](#)
- [Control](#)
- [DataElement](#)
- [Environment](#)
- [Exchange](#)
- [Function](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [MeasurementSet](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [PropertySet](#)
- [Resource](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInterface](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)
- [Responsibility](#)

- [PerformsInContext](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessOperation](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceMethod](#)
- [ResourceParameter](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Operation
- UML2.5Metamodel::Parameter

View Specifications::Personnel::States

Contains the diagrams that document the Personnel States Viewpoint.

View Specifications::Personnel::States::Personnel States

Stakeholders: Systems Engineers, Software Engineers.

Concerns: capture state-based behavior of an organizational resource.

Definition: it is a graphical representation of states of an organizational resource and how that organizational resource responds to various events and actions.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:32 - Personnel States

Elements

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [ResourceStateDescription](#)
- [Responsibility](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Personnel::Interaction Scenarios

Contains the diagrams that document the Personnel Interaction Scenarios Viewpoint.

View Specifications::Personnel::Interaction Scenarios::Personnel Interaction Scenarios

Stakeholders: Software Engineers, Systems Engineers.

Concerns: interactions between organizational resources (roles).

Definition: provides a time-ordered examination of the interactions between organizational resources.

Recommended Implementation: SysML Sequence Diagram, BPMN Collaboration Diagram.




Figure 8:33 - Personnel Interaction Scenarios

Elements

- [DataElement](#)
- [Function](#)
- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInteractionScenario](#)
- [ResourceMessage](#)
- [ResourceMethod](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Personnel::Constraints

Contains the diagrams that document the Personnel Constraints Viewpoint.

View Specifications::Personnel::Constraints::Personnel Constraints: Competence

Stakeholders: Systems engineers, Solution providers.

Concerns: allocation of competencies to actual posts.

Definition: specifies requirements for actual organizational resources – by linking competencies and actual posts.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:34 - Personnel Constraints: Competence

Elements

- [ActualOrganization](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualResponsibility](#)
- [ActualResponsibleResource](#)
- [Competence](#)
- [CompetenceForRole](#)
- [CompetenceToConduct](#)
- [Function](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ProvidesCompetence](#)
- [RequiresCompetence](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)

View Specifications::Personnel::Constraints::Personnel Constraints: Drivers

Stakeholders: Systems engineers, Solution providers, Human resources.

Concerns: optimization of organizational resource behavior.

Definition: captures the factors that affect, constrain and characterize organizational resource behavior as the basis for

performance predictions at the level of actual persons and actual organizations. It creates a bridge between static architectural definitions and behavior predictions through executable models.
 Recommended Implementation: tabular format, SysML Parametric Diagram, SysML Block Definition Diagram.




Figure 8:35 - Personnel Constraints: Drivers

Elements

- [ActualMeasurement](#)
- [ActualMeasurementSet](#)
- [Function](#)
- [IsCapableToPerform](#)
- [MeasurableElement](#)
- [Measurement](#)
- [MeasurementSet](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [ResourceConstraint](#)
- [ResourcePerformer](#)
- [Responsibility](#)
- [Rule](#)
- [SubjectOfResourceConstraint](#)

View Specifications::Personnel::Constraints::Personnel Constraints: Performance

Stakeholders: Human resources, solution providers.

Concerns: how well an actual organizational resource matches the needs of the actual organization.

- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
 - [Post](#)
 - [Process](#)
 - [ResourcePerformer](#)
 - [Responsibility](#)

View Specifications::Personnel::Roadmap

Contains the diagrams that document the Personnel Roadmap Viewpoint.

View Specifications::Personnel::Roadmap::Personnel Roadmap: Availability

Stakeholders: Human Resources, Training, Logisticians, Solution Providers.

Concerns: the staffing and training of resources.

Definition: defines the requirements and functions to ensure that actual persons with the right competencies, and in the right numbers, are available to fulfill actual posts.

Recommended Implementation: Timeline, SysML Block Definition Diagram.

- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Project](#)
- [ProjectMilestone](#)
- [PropertySet](#)
- [ResourceAsset](#)
- [ResourcePerformer](#)

View Specifications::Personnel::Roadmap::Personnel Roadmap: Evolution

Stakeholders: Human resources, Solution Providers.

Concerns: organizational structure changes over time.

Definition: provides an overview of how an organizational structure changes over time. It shows the structure of several organizational structures mapped against a timeline.

Recommended Implementation: timeline, SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:38 - Personnel Roadmap: Evolution

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)
- [VersionedElement](#)
- [VersionOfConfiguration](#)

- [VersionSuccession](#)
- [WholeLifeConfiguration](#)

View Specifications::Personnel::Roadmap::Personnel Roadmap: Forecast

Stakeholders: Human resources, Logisticians, Solution Providers.

Concerns: competencies and skills forecast.

Definition: defines the underlying current and expected supporting competencies and skills of organizational resources.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:39 - Personnel Roadmap: Forecast

Elements

- [ActualEnterprisePhase](#)
- [ActualPropertySet](#)
- [ActualState](#)
- [Asset](#)
- [Competence](#)
- [Forecast](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)
- [SubjectOfForecast](#)

View Specifications::Personnel::Traceability

Contains the diagrams that document the Personnel Traceability Viewpoint.

View Specifications::Personnel::Traceability::Personnel Traceability

Stakeholders: Systems Engineers, Enterprise Architects, Solution Providers, Business Architects.

Concerns: traceability between operational activities and functions that implements them.

Definition: depicts the mapping of functions (performed by organizational resources) to operational activities and thus identifies the transformation of an operational need into a purposeful function performed by an organizational resource or solution.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:40 - Personnel Traceability

Elements

- [Function](#)
- [Implements](#)
- [OperationalActivity](#)
- [ServiceFunction](#)

8.1.6 View Specifications::Resources

Stakeholders: Systems Engineers, Resource Owners, Implementers, Solution Providers, IT Architects.

Concerns: definition of solution architectures to implement operational requirements.

Definition: captures a solution architecture consisting of resources, e.g., organizational, software, artifacts, capability configurations, natural resources that implement the operational requirements. Further design of a resource is typically detailed in SysML or UML.

View Specifications::Resources::Taxonomy

Contains the diagrams that document the Resources Taxonomy Viewpoint.

View Specifications::Resources::Taxonomy::Resources Taxonomy

Stakeholders: Solution Providers, Systems Engineers, IT Architects, Implementers.

Concerns: resource types.

Definition: shows the taxonomy of types of resources.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:41 - Resources Taxonomy

Elements

- [Asset](#)
- [CapabilityConfiguration](#)
- [Implements](#)
- [Measurement](#)
- [NaturalResource](#)
- [OperationalAgent](#)
- [OperationalPerformer](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [PropertySet](#)
- [PropertySetGeneralization](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceAsset](#)
- [ResourceExchange](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Responsibility](#)
- [Software](#)
- [System](#)

View Specifications::Resources::Structure

Contains the diagrams that document the Resources Structure Viewpoint.

View Specifications::Resources::Structure::Resources Structure

Stakeholders: Systems Engineers, Resource Owners, Implementers, Solution Providers.

Concerns: reference the resource structure, connectors and interfaces in a specific context.

Definition: defines the physical resources, e.g., capability configuration(s)/system(s) and interactions necessary to implement a specific set of OperationalPerformer(s). Can be used to represent communications networks and pathways that link communications resources and provides details regarding their configuration.

Recommended Implementation: SysML Internal Block Diagram, SysML Block Definition Diagram.




Figure 8:42 - Resources Structure

Elements

- [Asset](#)
- [CapabilityConfiguration](#)
- [Measurement](#)
- [NaturalResource](#)
- [PhysicalResource](#)
- [PropertySet](#)
- [Protocol](#)
- [ProtocolImplementation](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceAsset](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceInterface](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [ResourcePort](#)

- [ResourceRole](#)
- [Software](#)

View Specifications::Resources::Connectivity

Contains the diagrams that document the Resources Connectivity Viewpoint.

View Specifications::Resources::Connectivity::Resources Connectivity

Stakeholders: Systems Engineers, IT Architects, Solution Providers, Implementers.

Concerns: capture the interactions between resources.

Definition: summarizes interactions between resources of information, systems, personnel, natural resources etc. and the functions that produce and consume them. Measurements can optionally be included.

Recommended Implementation: SysML Internal Block Diagram, tabular format.




Figure 8:43 - Resources Connectivity

Elements

- [CapabilityConfiguration](#)
- [DataElement](#)
- [Exchange](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [GeoPoliticalExtentType](#)
- [IsCapableToPerform](#)

- [MeasurableElement](#)
- [Measurement](#)
- [MeasurementSet](#)
- [NaturalResource](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [Process](#)
- [PropertySet](#)
- [Resource](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInterface](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)
- [ResourceSignal](#)
- [Software](#)
- [Technology](#)

View Specifications::Resources::Processes

Contains the diagrams that document the Resources Processes Viewpoint.

View Specifications::Resources::Processes::Resources Processes

Stakeholders: Solution Providers, Systems Engineers, IT Architects.

Concerns: captures activity based behavior and flows.

Definition: describes the functions that are normally conducted in the course of implementing operational activity(ies) in support of capability(ies). It describes the functions, their Inputs/Outputs, function actions and flows between them.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram.




Figure 8:44 - Resources Processes

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [DataElement](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [Implements](#)
- [OperationalActivity](#)
- [PerformsInContext](#)
- [PhysicalResource](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessParameter](#)
- [ProcessUsage](#)
- [ResourceArchitecture](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceParameter](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- UML2.5Metamodel::Activity
- UML2.5Metamodel::ActivityEdge
- UML2.5Metamodel::CallBehaviorAction
- UML2.5Metamodel::Parameter

View Specifications::Resources::Processes::Resources Processes BPMN Semantics

Stakeholders: Solution Providers, IT Architects.

Concerns: captures activity based behavior and flows using BPMN.

Definition: describes the functions that are normally conducted in the course of implementing operational activity(ies) in support of capability(ies). It describes the functions, their Inputs/Outputs, function actions and flows between them using BPMN.

Recommended Implementation: BPMN Process Diagram.




Figure 8:45 - Resources Processes BPMN Semantics

Elements

- [ActivityPerformableUnderCondition](#)
- [AssetRole](#)
- BPMN2Metamodel::BPMNMessage
- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::MessageFlow
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [DataElement](#)

- [Exchange](#)
- [ExchangeItem](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [Implements](#)
- [OperationalActivity](#)
- [PerformsInContext](#)
- [PhysicalResource](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessUsage](#)
- [ResourceArchitecture](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceParameter](#)
- [ResourcePerformer](#)
- [ResourceRole](#)

View Specifications::Resources::States

Contains the diagrams that document the Resources States Viewpoint.

View Specifications::Resources::States::Resources States

Stakeholders: Systems Engineers, Software Engineers.

Concerns: capture state-based behavior of a resource.

Definition: it is a graphical representation of states of a resource and how that resource responds to various events and actions.

Recommended Implementation: SysML State Machine Diagram.




Figure 8:46 - Resources States

Elements

- [ResourcePerformer](#)
- [ResourceStateDescription](#)
- [StateDescription](#)
- UML2.5Metamodel::StateMachine

View Specifications::Resources::Interaction Scenarios

Contains the diagrams that document the Resources Interaction Scenarios Viewpoint.

View Specifications::Resources::Interaction Scenarios::Resources Interaction Scenarios

Stakeholders: Software Engineers, Systems Engineers.

Concerns: interactions between resources (roles).

Definition: provides a time-ordered examination of the interactions between resources.

Recommended Implementation: SysML Sequence Diagram.




Figure 8:47 - Resources Interaction Scenarios

Elements

- [Function](#)
- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [ResourceExchange](#)
- [ResourceInteractionScenario](#)
- [ResourceMessage](#)
- [ResourceMethod](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- UML2.5Metamodel::Interaction
- UML2.5Metamodel::Lifeline
- UML2.5Metamodel::Message

View Specifications::Resources::Constraints

Contains the diagrams that document the Resources Constraints Viewpoint.

View Specifications::Resources::Constraints::Resources Constraints

Stakeholders: Systems Engineers, IT Architects, Solution Providers, Implementers.

Concerns: define limitations, constraints and performance parameters for resources, their interactions, performed functions, and data.

Definition: specifies traditional textual rules/non-functional requirements that are constraints on resources, their interactions, performed functions, and data. The addition of SysML parametrics provide a computational means of defining resource constraints within a specific context.

Recommended Implementation: tabular format, SysML Block Definition Diagram, SysML Parametric Diagram, OCL.




Figure 8:48 - Resources Constraints

Elements

- [ActualResource](#)
- [CapabilityConfiguration](#)
- [DataElement](#)
- [Function](#)
- [NaturalResource](#)
- [Organization](#)
- [OrganizationalResource](#)
- [Person](#)
- [PhysicalResource](#)
- [Post](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceConstraint](#)
- [ResourcePerformer](#)
- [ResourceRole](#)

- [Responsibility](#)
- [Rule](#)
- [SubjectOfResourceConstraint](#)

View Specifications::Resources::Roadmap

Contains the diagrams that document the Resources Roadmap Viewpoint.

View Specifications::Resources::Roadmap::Resources Roadmap: Evolution

Stakeholders: Systems Engineers, IT Architects, Solution Providers, Implements.

Concerns: resource structure changes over time.

Definition: provides an overview of how a resource structure changes over time. It shows the structure of several resources mapped against a timeline.

Recommended Implementation: timeline, SysML Block Definition Diagram, SysML Internal Block Diagram.




Figure 8:49 - Resources Roadmap: Evolution

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [ResourcePerformer](#)
- [VersionedElement](#)
- [VersionOfConfiguration](#)
- [VersionSuccession](#)
- [WholeLifeConfiguration](#)

View Specifications::Resources::Roadmap::Resources Roadmap: Forecast

Stakeholders: Solution Providers, Systems Engineers, IT Architects.

Concerns: technology forecast.

Definition: defines the underlying current and expected supporting technologies. Expected supporting technologies are those that can be reasonably forecast given the current state of technology, and expected improvements / trends.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:50 - Resources Roadmap: Forecast

Elements

- [ActualEnterprisePhase](#)
- [ActualPropertySet](#)
- [ActualState](#)
- [CapabilityConfiguration](#)
- [Forecast](#)
- [NaturalResource](#)
- [PhysicalResource](#)
- [ResourceArchitecture](#)
- [ResourceArtifact](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)
- [Software](#)
- [SubjectOfForecast](#)
- [Technology](#)

View Specifications::Resources::Traceability

Contains the diagrams that document the Resources Traceability Viewpoint.

View Specifications::Resources::Traceability::Resources Traceability

Stakeholders: Systems Engineers, Enterprise Architects, Solution Providers, Business Architects.

Concerns: traceability between operational activities and functions that implements them.

Definition: depicts the mapping of functions to operational activities and thus identifies the transformation of an operational need into a purposeful function performed by a resource or solution.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:51 - Resources Traceability

Elements

- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)
- [Function](#)
- [Implements](#)
- [IsCapableToPerform](#)
- [OperationalActivity](#)
- [OperationalAgent](#)
- [ResourcePerformer](#)
- [ServiceFunction](#)

8.1.7 View Specifications::Security

Stakeholders: Security Architects, Security Engineers. Systems Engineers, Operational Architects.

Concerns: addresses the security constraints and information assurance attributes that exist on exchanges between resources and OperationalPerformers

Definition: illustrates the security assets, security constraints, security controls, families, and measures required to address specific security concerns.

View Specifications::Security::Taxonomy

Contains the diagrams that document the Security Taxonomy Viewpoint.

View Specifications::Security::Taxonomy::Security Taxonomy

Stakeholders: Security Architects, Security Engineers.

Concerns: Security assets and security enclaves.

Definition: Defines the hierarchy of security assets and asset owners that are available to implement security, security constraints (policy, guidance, laws and regulations) and details where they are located (security enclaves).

Recommended Implementation: tabular format, SysML Block Definition Diagram.




Figure 8:52 - Security Taxonomy

Elements

- [ActualLocation](#)
- [Asset](#)
- [DataElement](#)
- [InformationElement](#)
- [LocationHolder](#)
- [Measurement](#)
- [MeasurementSet](#)
- [OperationalAgent](#)
- [OperationalArchitecture](#)
- [OperationalAsset](#)
- [OperationalMitigation](#)
- [OperationalPerformer](#)
- [PropertySet](#)
- [ResourceArchitecture](#)
- [ResourceAsset](#)
- [ResourceMitigation](#)
- [ResourcePerformer](#)

- [Risk](#)
- [SecurityAvailability](#)
- [SecurityCategory](#)
- [SecurityClassification](#)
- [SecurityClassificationKind](#)
- [SecurityEnclave](#)
- [SecurityIntegrity](#)
- [SecurityMeasurement](#)

View Specifications::Security::Structure

Contains the diagrams that document the Security Structure Viewpoint.

View Specifications::Security::Structure::Security Structure

Stakeholders: Security Architects, Security Engineers.

Concerns: The structure of security information and where it is used at the operational and resource level.

Definition: Captures the allocation of assets (operational and resource, information and data) across the security enclaves, shows applicable security controls necessary to protect organizations, systems and information during processing, while in storage (bdd), and during transmission (flows on an ibd). This view also captures Asset Aggregation and allocates the usage of the aggregated information at a location through the use of the SecurityProperty.

Recommended Implementation: SysML Internal Block Diagram, SysML Block Definition Diagram.




Figure 8:53 - Security Structure

Elements

- [Asset](#)
- [DataElement](#)
- [DataRole](#)
- [InformationElement](#)
- [InformationRole](#)
- [OperationalAgent](#)
- [OperationalAsset](#)
- [OperationalConnector](#)
- [OperationalExchange](#)

- [OperationalPerformer](#)
- [OperationalPort](#)
- [OperationalRole](#)
- [ResourceAsset](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)
- [SecurityCategory](#)

View Specifications::Security::Connectivity

Contains the diagrams that document the Security Connectivity Viewpoint.

View Specifications::Security::Connectivity::Security Connectivity

Stakeholders: Security Architects, Security Engineers.

Concerns: Addresses the security constraints and information assurance attributes that exist on exchanges across resources and across performers.

Definition: Lists security exchanges across security assets; the applicable security controls; and the security enclaves that house the producers and consumers of the exchanges. Measurements can optionally be included.

Recommended Implementation: SysML Internal Block Diagram, tabular format.




Figure 8:54 - Security Connectivity

Elements

- [Caveat](#)
- [MeasurableElement](#)
- [MeasurementSet](#)
- [OperationalAgent](#)
- [OperationalConnector](#)
- [OperationalExchange](#)
- [OperationalExchangeItem](#)
- [OperationalInterface](#)
- [OperationalPerformer](#)
- [OperationalPort](#)
- [OperationalRole](#)
- [ResourceConnector](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourceInterface](#)
- [ResourcePerformer](#)
- [ResourcePort](#)
- [ResourceRole](#)
- [SecurityConstraint](#)
- [SubjectOfSecurityConstraint](#)

View Specifications::Security::Processes

Contains the diagrams that document the Security Processes Viewpoint.

View Specifications::Security::Processes::Security Processes

Stakeholders: Security Architects, Security Engineers.

Concerns: The specification of the Security Control families, security controls, and measures required to address a specific security baseline.

Definition: Provides a set of Security Controls and any possible enhancements as applicable to assets. The activity diagram describes operational or resource level processes that apply (operational level) or implement (resource level) security controls/enhancements to assets located in enclaves and across enclaves. This Security Process view can be instantiated either as a variant of an activity/flow diagram or as a hierarchical work breakdown structure.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram, BPMN Process Diagram as described in Operational Processes and Resources Processes sections.

View Specifications::Security::Constraints::Security Constraints

Stakeholders: Security Architects, Security Engineers, Risk Analysts.

Concerns: (i) Security-related policy, guidance, laws and regulations as applicable to assets, (ii) threats, vulnerabilities, and risk assessments as applicable to assets.

Definition: (i) Specifies textual rules/non-functional requirements that are security constraints on resources, information and data (e.g. security-related in the form of rules (e.g. access control policy)). A common way of representing access control policy is through the use of XACML (eXtensible Access Control Markup Language), it is expected that implementations of UAF allow users to link security constraints to external files represented in XACML. (ii) Identifies risks, specifies risk likelihood, impact, asset criticality, other measurements and enables risk assessment.

Recommended Implementation: tabular or Matrix format, SysML Block Definition Diagram, SysML Parametric Diagram, or OCL.




Figure 8:56 - Security Constraints

Elements

- [ActualMeasurement](#)
- [ActualPropertySet](#)
- [ActualResource](#)

- [ActualResponsibleResource](#)
- [ActualRisk](#)
- [Affects](#)
- [AffectsInContext](#)
- [Asset](#)
- [AssetRole](#)
- [EnhancedSecurityControl](#)
- [Enhances](#)
- [Measurement](#)
- [Mitigates](#)
- [OperationalAgent](#)
- [OperationalRole](#)
- [OrganizationalResource](#)
- [OwnsRisk](#)
- [OwnsRiskInContext](#)
- [PropertySet](#)
- [Protects](#)
- [ProtectsInContext](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [Risk](#)
- [Rule](#)
- Satisfy
- [SecurityConstraint](#)
- [SecurityControl](#)
- [SecurityControlFamily](#)
- [SecurityProcess](#)
- [SubjectOfSecurityConstraint](#)

View Specifications::Security::Traceability

Contains the diagrams that document the Security Traceability Viewpoint.

View Specifications::Security::Traceability::Security Traceability

Stakeholders: Security Architects, Security Engineers, Risk Analysts.

Concerns: traceability between risk and risk owner, risk mitigations, and affected asset roles.

Definition: depicts the mapping of a risk to each of the following: risk owner, risk mitigations, and affected asset roles.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:57 - Security Traceability

Elements

- [Affects](#)
- [AffectsInContext](#)
- [Asset](#)
- [AssetRole](#)
- [DataRole](#)
- [InformationRole](#)
- [Mitigates](#)
- [OperationalRole](#)
- [OwnsRiskInContext](#)
- [Protects](#)
- [ProtectsInContext](#)
- [ResourceRole](#)
- [Risk](#)
- [Satisfy](#)
- [SecurityControl](#)

8.1.8 View Specifications::Projects

Stakeholders: PMs, Project Portfolio Managers, Enterprise Architects.

Concerns: project portfolio, projects and project milestones.

Definition: describes projects and project milestones, how those projects deliver capabilities, the organizations contributing to the projects and dependencies between projects.

View Specifications::Projects::Taxonomy

Contains the diagrams that document the Project Taxonomy Viewpoint.

View Specifications::Projects::Taxonomy::Project Taxonomy

Stakeholders: PMs, Project Portfolio Managers, Enterprise Architects. Concerns: types of projects and project milestones. Definition: shows the taxonomy of types of projects and project milestones. Recommended Implementation: SysML Block Definition Diagram.




Figure 8:58 - Project Taxonomy

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [MilestoneDependency](#)
- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ProjectSequence](#)

View Specifications::Projects::Structure

Contains the diagrams that document the Project Structure Viewpoint.

View Specifications::Projects::Structure::Project Structure

Stakeholders: PMs.

Concerns: relationships between types of projects and project milestones.

Definition: provides a template for an actual project(s) road map(s) to be implemented.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:59 - Project Structure

Elements

- [ActualOrganization](#)
- [ActualPost](#)
- [ActualProject](#)
- [ActualPropertySet](#)
- [ActualResponsibleResource](#)
- [ActualState](#)
- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ProjectTheme](#)
- [ResourceRole](#)
- [ResponsibleFor](#)
- [StatusIndicators](#)

View Specifications::Projects::Connectivity

Contains the diagrams that document the Project Connectivity Viewpoint.

View Specifications::Projects::Connectivity::Project Connectivity

Stakeholders: PMs.

Concerns: relationships between projects and project milestones.

Definition: shows how projects and project milestones are related in sequence.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:60 - Project Connectivity

Elements

- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ResourcePerformer](#)

View Specifications::Projects::Processes

Contains the diagrams that document the Project Processes Viewpoint.

View Specifications::Projects::Processes::Project Processes

Stakeholders: PMs.

Concerns: captures project tasks (ProjectActivities) and flows between them.

Definition: describes the ProjectActivities that are normally conducted in the course of projects to support capability(ies) and implement resources. It describes the ProjectActivities, their Inputs/Outputs, ProjectActivityActions and flows between them.

Recommended Implementation: SysML Activity Diagram, SysML Block Definition Diagram, BPMN Process Diagram as described in Resources Processes section.




Figure 8:61 - Project Processes

Elements

- [ActualProject](#)
- [DataElement](#)
- [Function](#)
- [FunctionAction](#)
- [FunctionEdge](#)
- [GeoPoliticalExtentType](#)
- [IsCapableToPerform](#)
- [Organization](#)
- [OrganizationalResource](#)
- [ProjectActivity](#)
- [ProjectActivityAction](#)
- [ResourceExchange](#)
- [ResourceExchangeItem](#)
- [ResourcePerformer](#)
- [ResourceRole](#)
- [ResourceSignal](#)

View Specifications::Projects::Roadmap

Contains the diagrams that document the Project Roadmap Viewpoint.

View Specifications::Projects::Roadmap::Project Roadmap

Stakeholders: PMs, Capability Owners, Solution Providers, Enterprise Architects.

Concerns: the product portfolio management; a planning of capability delivery.

Definition: provides a timeline perspective on programs or projects

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:62 - Project Roadmap

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [ActualProjectMilestoneRole](#)
- [ActualPropertySet](#)
- [ActualResource](#)
- [ActualState](#)
- [CapabilityConfiguration](#)
- [FieldedCapability](#)
- [MilestoneDependency](#)
- [Project](#)
- [ProjectMilestone](#)
- [ProjectMilestoneRole](#)
- [ProjectSequence](#)
- [ProjectStatus](#)
- [ProjectTheme](#)
- [ResourceArchitecture](#)
- [ResourcePerformer](#)
- [StatusIndicators](#)

View Specifications::Projects::Traceability

Contains the diagrams that document the Project Traceability Viewpoint.

View Specifications::Projects::Traceability::Project Traceability

Stakeholders: PMs, Project Portfolio Managers, Enterprise Architects.

Concerns: traceability between capabilities and projects that deliver them.

Definition: depicts the mapping of projects to capabilities and thus identifies the transformation of a capability(ies) into a purposeful implementation via projects.

Recommended Implementation: Matrix format, SysML Block Definition Diagram.




Figure 8:63 - Project Traceability

Elements

- [ActualProject](#)
- [ActualProjectMilestone](#)
- [ActualResource](#)
- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)
- [ResourcePerformer](#)

8.1.9 View Specifications::Standards

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: technical and non-technical Standards applicable to the architecture.

Definition: shows the technical, operational, and business Standards applicable to the architecture. Defines the underlying current and expected Standards.

View Specifications::Standards::Taxonomy

Contains the diagrams that document the Standards Taxonomy Viewpoint.

View Specifications::Standards::Taxonomy::Standards Taxonomy

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: technical and non-technical standards, guidance and policy applicable to the architecture.

Definition: shows the taxonomy of types of technical, operational, and business standards, guidance and policy applicable to the architecture.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:64 - Standards Taxonomy

Elements

- [ActualOrganization](#)
- [CapabilityConfiguration](#)
- [Protocol](#)
- [ProtocolStack](#)
- [ResourceArchitecture](#)
- [ResourcePerformer](#)
- [Standard](#)
- [StandardOperationalActivity](#)
- [UAFElement](#)

View Specifications::Standards::Structure

Contains the diagrams that document the Standards Structure Viewpoint.

View Specifications::Standards::Structure::Standards Structure

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects.
 Concerns: the specification of the protocol stack used in the architecture.
 Definition: shows the composition of standards required to achieve the architecture's objectives.
 Recommended Implementation: SysML Internal Block Diagram.




Figure 8:65 - Standards Structure

Elements

- [Protocol](#)
- [ProtocolLayer](#)
- [ProtocolStack](#)
- [Standard](#)

View Specifications::Standards::Roadmap

Contains the diagrams that document the Standards Roadmap Viewpoint.

View Specifications::Standards::Roadmap::Standards Roadmap

Stakeholders: Solution Providers, Systems Engineers, Systems Architects, Software Engineers, Business Architects.
 Concerns: expected changes in technology-related standards and conventions, operational standards, or business standards and conventions.

Definition: defines the underlying current and expected standards. Expected standards are those that can be reasonably forecast given the current state of technology, and expected improvements / trends.

Recommended Implementation: timeline, tabular format, SysML Block Definition Diagram.




Figure 8:66 - Standards Roadmap

Elements

- [ActualEnterprisePhase](#)
- [Forecast](#)
- [Protocol](#)
- [Standard](#)
- [SubjectOfForecast](#)

View Specifications::Standards::Traceability

Contains the diagrams that document the Standards Traceability Viewpoint.

View Specifications::Standards::Traceability::Standards Traceability

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: standards that need to be taken in account to ensure the interoperability of the implementation of architectural elements.

Definition: shows the applicability of standards to specific elements in the architecture.

Recommended Implementation: tabular format, matrix format, SysML Block Definition Diagram.




Figure 8:67 - Standards Traceability

Elements

- [Protocol](#)
- [Standard](#)
- [UAFElement](#)

8.1.10 View Specifications::Actual Resources

Stakeholders: Solution Providers, Systems Engineers, Business Architects, Human Resources.

Concerns: the analysis, e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations.

Definition: illustrates the expected or achieved actual resource configurations and actual relationships between them.

View Specifications::Actual Resources::Structure

Contains the diagrams that document the Actual Resources Structure Viewpoint.

View Specifications::Actual Resources::Structure::Actual Resources Structure

Stakeholders: Solution Providers, Systems Engineers, Business Architects.

Concerns: the analysis, e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations as it provides a means to capture different solution architectures. The detailed analysis (trade-off, what-if etc.) is carried out using the Resource Constraints view.

Definition: illustrates the expected or achieved actual resource configurations required to meet an operational need.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:68 - Actual Resources Structure

Elements

- [ActualOrganization](#)
- [ActualOrganizationalResource](#)
- [ActualPerson](#)
- [ActualPost](#)
- [ActualResource](#)
- [ActualResponsibility](#)
- [ActualResponsibleResource](#)
- [CapabilityConfiguration](#)
- [FieldedCapability](#)
- [Organization](#)
- [Person](#)
- [Post](#)
- [ResourcePerformer](#)
- [Responsibility](#)

View Specifications::Actual Resources::Connectivity

Contains the diagrams that document the Actual Resources Connectivity Viewpoint.

View Specifications::Actual Resources::Connectivity::Actual Resources Connectivity

Stakeholders: Solution Providers, Systems Engineers, Business Architects.

Concerns: the communication of actual resource.

Definition: illustrates the actual resource configurations and actual relationships between them.

Recommended Implementation: tabular format, SysML Block Definition Diagram, SysML Internal Block Diagram, SysML Sequence Diagram.




Figure 8:70 - Actual Resources Traceability

Elements

- [ActualResource](#)
- [Capability](#)
- [CapableElement](#)
- [Exhibits](#)

8.1.11 View Specifications::Dictionary

Stakeholders: Architects, users of the architecture, Capability Owners, Systems Engineers, Solution Providers.

Concerns: Definitions for all the elements in the architecture, libraries of environments and measurements.

Definition: Presents all the elements used in an architecture. Can be used specifically to capture:

- a. Elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.
- b. Measurable properties that can be used to support analysis such as KPIs, MoEs, TPIs etc.

View Specifications::Dictionary::Dictionary

Stakeholders: Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: provides a central reference for a given architecture's data and metadata. It enables the set of architecture description to stand alone, with minimal reference to outside resources.

Definition: contains definitions of terms used in the given architecture. It consists of textual definitions in the form of a glossary, their taxonomies, and their metadata (i.e., data about architecture data), including metadata for any custom-tailored views. Architects should use standard terms where possible (i.e., terms from existing, approved dictionaries, glossaries, and lexicons).

Recommended Implementation: text, table format.




Figure 8:71 - Dictionary

Elements

- [Alias](#)
- [Definition](#)
- [Information](#)
- [SameAs](#)
- [UAFElement](#)

8.1.12 View Specifications::Summary & Overview

Stakeholders: Executives, PMs, Enterprise Architects.

Concerns: executive-level summary information in a consistent form.

Definition: provides executive-level summary information in a consistent form that allows quick reference and comparison between architectural descriptions. Includes assumptions, constraints, and limitations that may affect high-level decisions relating to an architecture-based work program.

View Specifications::Summary & Overview::Summary & Overview

Stakeholders: Decision makers, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: quick overview of an architecture description and summary of analysis. In the initial phases of architecture development, it serves as a planning guide. Upon completion of an architecture, it provides a summary of findings, and any conducted analysis.

Definition: provides executive-level summary information in a consistent form that allows quick reference and comparison among architectures. The Summary and Overview includes assumptions, constraints, and limitations that may affect high-level decision processes involving the architecture.

Recommended Implementation: text, free form diagram, table format.




Figure 8:72 - Summary & Overview

Elements

- [ActualEnterprisePhase](#)
- [ActualOrganizationalResource](#)
- [ArchitecturalDescription](#)
- [ArchitecturalReference](#)
- [Architecture](#)
- [ArchitectureMetadata](#)
- [Concern](#)
- [EnterprisePhase](#)
- [Metadata](#)
- [OperationalArchitecture](#)
- [OrganizationalResource](#)
- [ResourceArchitecture](#)
- [Stakeholder](#)
- [View](#)
- [Viewpoint](#)
- [WholeLifeEnterprise](#)

8.1.13 View Specifications::Requirements

Stakeholders: Requirement Engineers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: requirements traceability.

Definition: used to represent requirements, their properties, and relationships (trace, verify, satisfy, refine) to UAF architectural elements.

View Specifications::Requirements::Requirements

Stakeholders: Requirement Engineers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: provides a central reference for a set of stakeholder needs expressed as requirements, their relationship (via traceability) to more detailed requirements and the solution described by the architecture that will meet those requirements.

Definition: used to represent requirements, their properties, and relationships (trace, verify, satisfy, refine) between each other and to UAF architectural elements.

Recommended Implementation: SysML Requirement Diagram, tabular format, matrix format.




Figure 8:73 - Requirements

Elements

- Refine
- Requirement
- Satisfy
- Trace
- [UAFElement](#)
- Verify

8.1.14 View Specifications::Information

Stakeholders: Data Modelers, Software Engineers, Systems Engineers

Concerns: address the information perspective on operational, service, and resource architectures.

Definition: allows analysis of an architecture's information and data definition aspect, without consideration of implementation specific issues.

Recommended Implementation: SysML Block Definition Diagram.

View Specifications::Information::Information Model

Stakeholders: Data Modelers, Software Engineers, Systems Engineers

Concerns: address the information perspective on operational, service, and resource architectures.

Definition: allows analysis of an architecture's information and data definition aspect, without consideration of implementation specific issues.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:74 - Information Model

Elements

- [DataElement](#)
- [DataModel](#)
- [DataRole](#)
- [Implements](#)
- [InformationElement](#)
- [InformationRole](#)
- [OperationalAsset](#)
- [ResourceAsset](#)

8.1.15 View Specifications::Parameters

Stakeholders: Capability owners, Systems Engineers, Solution Providers.

Concerns: identifies measurable properties that can be used to support engineering analysis and environment for the Capabilities

Definition: Shows the measurable properties of something in the physical world and elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.

View Specifications::Parameters::Parameters: Environment

Stakeholders: Capability owners, Systems Engineers, Solution Providers.

Concerns: defines the environment for the capabilities.

Definition: shows the elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.

Recommended Implementation: SysML Block Definition Diagram.




Figure 8:75 - Parameters: Environment

Elements

- [ActivityPerformableUnderCondition](#)
- [ActualCondition](#)
- [ActualEnvironment](#)
- [ActualLocation](#)
- [ActualPropertySet](#)
- [ActualResource](#)
- [Asset](#)
- [Condition](#)
- [Environment](#)
- [EnvironmentProperty](#)
- [GeoPoliticalExtentType](#)
- [Location](#)
- [LocationHolder](#)
- [OperationalRole](#)
- [Process](#)
- [ResourcePerformer](#)
- [ResourceRole](#)

View Specifications::Parameters::Parameters: Measurements

Stakeholders: Capability owners, Systems Engineers, Solution Providers.

Concerns: identifies measurable properties that can be used to support analysis such as KPIs, MoEs, TPIs etc.

Definition: Shows the measurable properties of something in the physical world, expressed in amounts of a unit of measure that can be associated with any element in the architecture.

Recommended Implementation: SysML Block Definition Diagram.

8.1.16 View Specifications::Other

Contains the diagrams that document the use of BPMN, NIEM, IEPPV in the context of UAF.

View Specifications::Other::BPMN

Stakeholders: Business Architects, Enterprise Architects

Concerns: captures activity based behavior and flows.

Definition: describes the activities that are normally conducted in the course of achieving business goals that support a capability. It describes operational activities, their Inputs/Outputs, operational activity actions and flows between them using BPMN.

Recommended Implementation: BPMN Process Diagram.




Figure 8:77 - BPMN

Elements

- [AssetRole](#)
- BPMN2Metamodel::BPMNMessage
- BPMN2Metamodel::CallActivity
- BPMN2Metamodel::MessageFlow
- BPMN2Metamodel::Process
- BPMN2Metamodel::ResourceRole
- BPMN2Metamodel::SequenceFlow
- [Exchange](#)

- [ExchangeItem](#)
- [InteractionMessage](#)
- [InteractionRole](#)
- [InteractionScenario](#)
- [Process](#)
- [ProcessEdge](#)
- [ProcessUsage](#)

View Specifications::Other::IEPPV

Stakeholders: Data Modelers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects, information architects.

Concerns: information exchanges, information interfaces, information interoperability, information sharing and safeguarding.

Definition: UAFP supports information modeling and traceability to IEPPV model elements using the IEPPV-defined elements: Message, SemanticElement, and FilteredSemanticElement, used to represent data, properties/attributes, structure, format, and relationships. The IEPPV profile enables the specification of the policies, rules and constraints governing the packaging (assembly, transformation, marking, redaction) of data elements conforming to information sharing and safeguarding requirements. The IEPPV profile also governs the processing (parsing, transformation, and marshalling) received information and data element.

Recommended Implementation: UML Class Diagram, SysML Block Diagram.




Figure 8:78 - IEPPV

Elements

- Abstraction
- FilteredSemanticElement
- [InformationElement](#)
- InformationSpecification
- Message
- [OperationalExchange](#)
- [OperationalExchangeItem](#)

View Specifications::Other::NIEM

Stakeholders: Data Modelers, Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: information exchanges, information interoperability, data schema.

Definition: A specification representing the structure, semantics, and relationships of data objects that satisfy an information exchange requirement. Used for organizing and packaging Model Package Descriptions (MPDs) and Information Exchange Package Documentation (IEPD) as defined by the National Information Exchange Model (NIEM). An IEPD is a type of MPD. The NIEM MPD defines an Enterprise Information Exchange Model (EIEM) as an MPD that contains NIEM-conforming schemas that define and declare data components to be consistently reused in the IEPDs of an enterprise. An EIEM is a collection of schemas organized into a collection of subset schemas and one or more extension schemas. An information sharing enterprise creates and maintains an EIEM.

Recommended Implementation: UML Class Diagram, SysML Block Diagram.




Figure 8:79 - NIEM

Elements

- Abstraction
- [DataElement](#)
- [DataModel](#)
- DataObject
- [InformationElement](#)
- InformationModel

This page intentionally left blank.

9 Domain Metamodel (DMM) Elements

9.1 Domain MetaModel

This package contains the elements of the DMM.

9.1.1 Domain MetaModel::Metadata

Stakeholders: Enterprise Architects, people who want to discover the architecture, Technical Managers.

Concerns: Captures meta-data relevant to the entire architecture

Definition: Provide information pertinent to the entire architecture. Present supporting information rather than architectural models.

Domain MetaModel::Metadata::Taxonomy

ArchitectureMetadata

Package: Taxonomy

isAbstract: No

Generalization: [Metadata](#)

Description

Information associated with an ArchitecturalDescription, that supplements the standard set of tags used to summarize the Architecture. It states things like what methodology was used, notation, etc.




Figure 9:1 - ArchitectureMetadata

InteractionScenarioGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

An InteractionScenarioGeneralization is a taxonomic relationship between a more general InteractionScenario and a more specific InteractionScenario.




Figure 9:2 - InteractionScenarioGeneralization

Metadata

Package: Taxonomy

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A comment that can be applied to any element in the architecture. The attributes associated with this element details the relationship between the element and its related dublinCoreElement, metaDataScheme, category and name. This allows the element to be referenced using the Semantic Web.




Figure 9:3 - Metadata

Attributes

category : String[0..1]	Defines the category of a Metadata element example: http://purl.org/dc/terms/abstract .
dublinCoreTag : String[0..1]	A metadata category that is a DublinCore tag.
metaDataScheme : String[0..1]	A representation scheme that defines a set of Metadata.
name : String[0..1]	The name of the Metadata.

ProcessGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

A ProcessGeneralization is a taxonomic relationship between a more general Process and a more specific Process.




Figure 9:4 - ProcessGeneralization

PropertySetGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

A PropertySetGeneralization is a taxonomic relationship between a more general PropertySet and a more specific PropertySet.




Figure 9:5 - PropertySetGeneralization

StateDescriptionGeneralization

Package: Taxonomy

isAbstract: No

Generalization: UML2.5Metamodel::Generalization, [MeasurableElement](#)

Description

A StateDescriptionGeneralization is a taxonomic relationship between a more general StateDescription and a more specific StateDescription.




Figure 9:6 - StateDescriptionGeneralization

Domain MetaModel::Metadata::Structure

EnvironmentProperty

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of an Environment that is typed by a Condition. The kinds of Condition that can be represented are Location, GeoPoliticalExtentType and Environment.




Figure 9:7 - EnvironmentProperty

Domain MetaModel::Metadata::Connectivity

Exchange

Package: Connectivity

isAbstract: Yes

Generalization: [MeasurableElement](#), [BPMN2Metamodel::MessageFlow](#), [SubjectOfSecurityConstraint](#)

Description

Abstract tuple, grouping OperationalExchanges and ResourceExchanges that exchange Resources.




Figure 9:8 - Exchange

Exchangeltem

Package: Connectivity

isAbstract: Yes

Generalization: BPMN2Metamodel::BPMNMessage

Description

An abstract grouping for elements that defines the types of elements that can be exchanged between Assets and conveyed by an Exchange.




Figure 9:9 - Exchangeltem

Resource

Package: Connectivity

isAbstract: Yes

Generalization: [PropertySet](#)

Description

Abstract type grouping all elements that can be conveyed by an Exchange.




Figure 9:10 - Resource

Domain MetaModel::Metadata::Processes

ActivityPerformableUnderCondition

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

The ActualCondition under which an Activity is performed.




Figure 9:11 - ActivityPerformableUnderCondition

IsCapableToPerform

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple defining the traceability between the structural elements to the Activities that they can perform.




Figure 9:12 - IsCapableToPerform

PerformsInContext

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that relates an OperationalAction to an OperationalRole, or a FunctionAction to a ResourceRole. It indicates that the action can be carried out by the role when used in a specific context or configuration.




Figure 9:13 - PerformsInContext

Process

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, BPMN2Metamodel::Process

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:14 - Process




Figure 9:15 - Process

ProcessEdge

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, UML2.5Metamodel::ActivityEdge, BPMN2Metamodel::SequenceFlow

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:16 - ProcessEdge

ProcessOperation

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, UML2.5Metamodel::Operation

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:17 - ProcessOperation

ProcessParameter

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, UML2.5Metamodel::CallBehaviorAction, UML2.5Metamodel::Parameter

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:18 - ProcessParameter

ProcessUsage

Package: Processes

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, UML2.5Metamodel::CallBehaviorAction, BPMN2Metamodel::CallActivity

Description

An abstract type that represents a behavior or process (i.e., a Function or OperationalActivity) that can be performed by a Performer.




Figure 9:19 - ProcessUsage

Domain MetaModel::Metadata::States

StateDescription

Package: States

isAbstract: Yes

Generalization: UML2.5Metamodel::StateMachine

Description

An abstract type that represents a state machine (i.e., an OperationalStateDescription or ResourceStateDescription), depicting how the Asset responds to various events and the actions.




Figure 9:20 - StateDescription

Domain MetaModel::Metadata::Interaction Scenarios

InteractionMessage

Package: Interaction Scenarios

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, BPMN2Metamodel::Process, UML2.5Metamodel::Interaction, UML2.5Metamodel::Message

Description

An abstract type that groups several types of messages used in the InteractionScenario.

InteractionRole

Package: Interaction Scenarios

isAbstract: Yes

Generalization: BPMN2Metamodel::ResourceRole

Description

An abstract type that represents an individual participant in the InteractionScenario.




Figure 9:21 - InteractionRole

InteractionScenario

Package: Interaction Scenarios

isAbstract: Yes

Generalization: [MeasurableElement](#), UML2.5Metamodel::Activity, BPMN2Metamodel::Process, UML2.5Metamodel::Interaction

Description

An abstract type that specifies interactions between Assets, like ResourcePerformers, and ServiceSpecifications.




Figure 9:22 - InteractionScenario

Domain MetaModel::Metadata::Information

Information

Package: Information

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A comment that describes the state of an item of interest in any medium or form -- and is communicated or received.




Figure 9:23 - Information

Domain MetaModel::Metadata::Constraints

Rule

Package: Constraints

isAbstract: Yes

Generalization: [MeasurableElement](#)

Description

An abstract type for all types of constraint (i.e., an OperationalConstraint could detail the rules of accountancy best practice).




Figure 9:24 - Rule

Domain MetaModel::Metadata::Traceability

ArchitecturalReference

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that specifies that one architectural description refers to another.




Figure 9:25 - ArchitecturalReference

Implements

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that defines how an element in the upper layer of abstraction is implemented by a semantically equivalent element (for example tracing the Functions to the OperationalActivities) in the lower level of abstraction.




Figure 9:26 - Implements

9.1.2 Domain MetaModel::Strategic

Domain MetaModel::Strategic::Taxonomy

Capability

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#), [Desirer](#)

Description

A high-level specification of the enterprise's ability to execute a specified course of action.




Figure 9:27 - Capability

CapabilityGeneralization

Package: Taxonomy

isAbstract: No

Generalization: [PropertySetGeneralization](#)

Description

A CapabilityGeneralization is a taxonomic relationship between a more general Capability and a more specific Capability.



Figure 9:28 - CapabilityGeneralization

Domain MetaModel::Strategic::Structure

ActualEnduringTask

Package: Structure

isAbstract: No

Generalization: [CapableElement](#), [ActualPropertySet](#)

Description

An actual undertaking recognized by an enterprise as being essential to achieving its goals - i.e., a strategic specification of what the enterprise does.




Figure 9:29 - ActualEnduringTask

ActualEnterprisePhase

Package: Structure

isAbstract: No

Generalization: [CapableElement](#), [ActualPropertySet](#), [Achiever](#)

Description

An individual that describes the phase of an actual enterprise endeavor.




Figure 9:30 - ActualEnterprisePhase

CapabilityRole

Package: Structure

isAbstract: No

Generalization: [PropertySet](#), [Desirer](#), [MeasurableElement](#)

Description

A high-level specification of the enterprise's ability to execute a specified course of action.




Figure 9:31 - CapabilityRole

EnduringTask

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A type of template behavior recognized by an enterprise as being essential to achieving its goals - i.e., a template for a strategic specification of what the enterprise does.




Figure 9:32 - EnduringTask

EnterpriseGoal

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A statement about a state or condition of the enterprise to be brought about or sustained through appropriate Means. An EnterpriseGoal amplifies an EnterpriseVision that is, it indicates what must be satisfied on a continuing basis to effectively attain the EnterpriseVision. BMM: OMG dtc-13-08-24.




Figure 9:33 - EnterpriseGoal

Attributes

benefits : String[0..*] A description of the usefulness of the Goal in terms of why the state or condition of the Enterprise is worth attaining.

EnterprisePhase

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A type of a current or future state of the enterprise.




Figure 9:34 - EnterprisePhase

EnterpriseVision

Package: Structure

isAbstract: No

Generalization: [PropertySet](#)

Description

A Vision describes the future state of the enterprise, without regard to how it is to be achieved. BMM: OMG dtc-13-08-24.




Figure 9:35 - EnterpriseVision

StructuralPart

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A current or future state of the wholeLifeEnterprise or another EnterprisePhase.




Figure 9:36 - StructuralPart

TemporalPart

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A current or future state of the wholeLifeEnterprise or another EnterprisePhase.




Figure 9:37 - TemporalPart

VisionStatement

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A type of comment that describes the future state of the enterprise, without regard to how it is to be achieved. BMM: OMG dtc-13-08-24.




Figure 9:38 - VisionStatement

WholeLifeEnterprise

Package: Structure

isAbstract: No

Generalization: [EnterprisePhase](#)

Description

A WholeLifeEnterprise is a purposeful endeavor of any size involving people, organizations and supporting systems. It is made up of TemporalParts and StructuralParts.




Figure 9:39 - WholeLifeEnterprise

Domain MetaModel::Strategic::Connectivity

CapabilityDependency

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that one CapabilityDependency is dependent from another.




Figure 9:40 - CapabilityDependency

CapabilityRoleDependency

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)




Figure 9:41 - CapabilityRoleDependency

Domain MetaModel::Strategic::States

AchievedEffect

Package: States

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that exists between an ActualState (e.g., observed/measured during testing) of an element that attempts to achieve a DesiredEffect and an Achiever.




Figure 9:42 - AchievedEffect

Achiever

Package: States

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An ActualResource, ActualProject or ActualEnterprisePhase that can deliver a DesiredEffect.




Figure 9:43 - Achiever

DesiredEffect

Package: States

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating the Desirer (a Capability or OrganizationalResource) to an ActualState.




Figure 9:44 - DesiredEffect

Desirer

Package: States

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract type used to group architecture elements that might desire a particular effect.




Figure 9:45 - Desirer

Domain MetaModel::Strategic::Traceability

CapabilityForTask

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a Capability is required in order for an Enterprise to conduct a phase of an EnduringTask.




Figure 9:46 - CapabilityForTask

CapableElement

Package: Traceability

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type that represents a structural element that can exhibit capabilities.




Figure 9:47 - CapableElement

Exhibits

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that exists between a CapableElement and a Capability that it meets under specific environmental conditions.




Figure 9:48 - Exhibits

MapsToCapability

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple denoting that an Activity contributes to providing a Capability.




Figure 9:49 - MapsToCapability

OrganizationInEnterprise

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating an ActualOrganization to an ActualEnterprisePhase to denote that the ActualOrganization plays a role or is a stakeholder in an ActualEnterprisePhase.




Figure 9:50 - OrganizationInEnterprise

9.1.3 Domain MetaModel::Operational

Domain MetaModel::Operational::Taxonomy

ArbitraryConnector

Package: Taxonomy

isAbstract: No

Generalization: [MeasurableElement](#)

Description

Represents a visual indication of a connection used in high level operational concept diagrams.




Figure 9:51 - ArbitraryConnector

ConceptItem

Package: Taxonomy

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract, an item which may feature in a HighLevelOperationalConcept.




Figure 9:52 – ConceptItem

HighLevelOperationalConcept

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#)

Description

Describes the Resources and Locations required to meet an operational scenario from an integrated systems point of view. It is used to communicate overall quantitative and qualitative system characteristics to stakeholders.




Figure 9:53 - HighLevelOperationalConcept

Domain MetaModel::Operational::Structure

KnownResource

Package: Structure

isAbstract: No

Generalization: [OperationalPerformer](#), [ResourcePerformer](#)

Description

Asserts that a known ResourcePerformer constrains the implementation of the OperationalPerformer that plays the role in the OperationalArchitecture.




Figure 9:54 - KnownResource

OperationalAgent

Package: Structure

isAbstract: Yes

Generalization: [SubjectOfOperationalConstraint](#), [CapableElement](#), [OperationalAsset](#), [Desirer](#)

Description

An abstract type grouping OperationalArchitecture and OperationalPerformer.




Figure 9:55 - OperationalAgent

OperationalArchitecture

Package: Structure

isAbstract: No

Generalization: [OperationalAgent](#), [Architecture](#)

Description

A type used to denote a model of the Architecture, described from the Operational perspective.




Figure 9:56 - OperationalArchitecture

OperationalMethod

Package: Structure

isAbstract: No

Generalization: [ProcessOperation](#)

Description

A behavioral feature of an OperationalAgent whose behavior is specified in an OperationalActivity.




Figure 9:57 - OperationalMethod

OperationalParameter

Package: Structure

isAbstract: No

Generalization: [ProcessParameter](#)

Description

A type that represents inputs and outputs of an OperationalActivity. It is typed by an OperationalExchangeItem.




Figure 9:58 - OperationalParameter

OperationalPerformer

Package: Structure

isAbstract: No

Generalization: [OperationalAgent](#)

Description

A logical entity that IsCapableToPerform OperationalActivities which produce, consume and process Resources.




Figure 9:59 - OperationalPerformer

OperationalRole

Package: Structure

isAbstract: No

Generalization: [LocationHolder](#), [AssetRole](#), [InteractionRole](#)

Description

Usage of an OperationalPerformer or OperationalArchitecture in the context of another OperationalPerformer or OperationalArchitecture. Creates a whole-part relationship.




Figure 9:60 - OperationalRole

ProblemDomain

Package: Structure

isAbstract: No

Generalization: [OperationalRole](#)

Description

A property associated with an OperationalArchitecture, used to specify the scope of the problem.




Figure 9:61 - ProblemDomain

Domain MetaModel::Operational::Connectivity

OperationalConnector

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A Connector that goes between OperationalRoles representing a need to exchange Resources. It can carry a number of OperationalExchanges.




Figure 9:62 - OperationalConnector

OperationalExchange

Package: Connectivity

isAbstract: No

Generalization: [Exchange](#), [SubjectOfOperationalConstraint](#)

Description

Asserts that a flow can exist between OperationalPerformers (i.e., flows of information, people, materiel, or energy).




Figure 9:63 - OperationalExchange

Attributes

trustLevel : Real[0..1] Captures the directional arbitrary level of trust related to an OperationalExchange between two OperationalPerformers.

OperationalExchangeItem

Package: Connectivity

isAbstract: Yes

Generalization: [Resource](#), [SubjectOfSecurityConstraint](#), [ExchangeItem](#)

Description

An abstract grouping for elements that defines the types of elements that can be exchanged between OperationalPerformers and conveyed by an OperationalExchange.




Figure 9:64 - OperationalExchangeItem

OperationalInterface

Package: Connectivity

isAbstract: No

Generalization: [PropertySet](#)

Description

A declaration that specifies a contract between the OperationalPerformer it is related to, and any other OperationalPerformers it can interact with.




Figure 9:65 - OperationalInterface

OperationalPort

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An interaction point for an OperationalAgent through which it can interact with the outside environment and which is defined by an OperationalInterface.




Figure 9:66 - OperationalPort

OperationalSignal

Package: Connectivity

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [OperationalExchangeItem](#)

Description

An item of information that flows between OperationalPerformers and is produced and consumed by the OperationalActivities that the OperationalPerformers are capable of performing (see IsCapableToPerform).




Figure 9:67 - OperationalSignal

Domain MetaModel::Operational::Processes

OperationalActivity

Package: Processes

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [Process](#)

Description

An Activity that captures a logical process, specified independently of how the process is carried out.




Figure 9:68 - OperationalActivity

OperationalActivityAction

Package: Processes

isAbstract: No

Generalization: [ProcessUsage](#)

Description

A call of an OperationalActivity in the context of another OperationalActivity.




Figure 9:69 - OperationalActivityAction

OperationalActivityEdge

Package: Processes

isAbstract: Yes

Generalization: [ProcessEdge](#)

Description

A tuple that shows the flow of Resources (objects/information) between OperationalActivityActions.




Figure 9:70 - OperationalActivityEdge

StandardOperationalActivity

Package: Processes

isAbstract: No

Generalization: [OperationalActivity](#)

Description

A sub-type of OperationalActivity that is a standard operating procedure.




Figure 9:71 - StandardOperationalActivity

Domain MetaModel::Operational::States

OperationalStateDescription

Package: States

isAbstract: No

Generalization: [MeasurableElement](#), [StateDescription](#)

Description

A state machine describing the behavior of an OperationalPerformer, depicting how the OperationalPerformer responds to various events and the actions.




Figure 9:72 - OperationalStateDescription

Domain MetaModel::Operational::Interaction Scenarios

OperationalInteractionScenario

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionScenario](#)

Description

A specification of the interactions between OperationalPerformers in an OperationalArchitecture.




Figure 9:73 - OperationalInteractionScenario

OperationalMessage

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionMessage](#)

Description

Message for use in an OperationalInteractionScenario which carries any of the subtypes of OperationalExchange.




Figure 9:74 - OperationalMessage

Domain MetaModel::Operational::Information

InformationElement

Package: Information

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [OperationalAsset](#), [OperationalExchangeItem](#)

Description

An item of information that flows between OperationalPerformers and is produced and consumed by the OperationalActivities that the OperationalPerformers are capable to perform (see IsCapableToPerform).




Figure 9:75 - InformationElement

Domain MetaModel::Operational::Constraints

OperationalConstraint

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A Rule governing an operational architecture element, i.e., OperationalPerformer, OperationalActivity, InformationElement etc.




Figure 9:76 - OperationalConstraint

SubjectOfOperationalConstraint

Package: Constraints

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping element that can be the subject of an OperationalConstraint.




Figure 9:77 - SubjectOfOperationalConstraint

9.1.4 Domain MetaModel::Services

Stakeholders: Enterprise Architects, Solution Providers, Systems Engineers, Software Architects, Business Architects.

Concerns: specifications of services required to exhibit a Capability.

Definition: shows Service Specifications and required and provided service levels of these specifications required to exhibit a Capability or to support an Operational Activity.

Domain MetaModel::Services::Taxonomy

ServiceSpecification

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#), [VersionedElement](#), [CapableElement](#)

Description

The specification of a set of functionalities provided by one element for the use of others.




Figure 9:78 - ServiceSpecification

ServiceSpecificationGeneralization

Package: Taxonomy

isAbstract: No

Generalization: [PropertySetGeneralization](#)

Description

A ServiceSpecificationGeneralization is a taxonomic relationship between a more general ServiceSpecification and a more specific ServiceSpecification.




Figure 9:79 - ServiceSpecificationGeneralization

Domain MetaModel::Services::Structure

ServiceConnector

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A channel for exchange between two ServiceSpecifications. Where one acts as the consumer of the other.




Figure 9:80 - ServiceConnector

ServiceMethod

Package: Structure

isAbstract: No

Generalization: [ProcessOperation](#)

Description

A behavioral feature of a ServiceSpecification whose behavior is specified in a ServiceFunction.




Figure 9:81 - ServiceMethod

ServiceParameter

Package: Structure

isAbstract: No

Generalization: [ProcessParameter](#)

Description

A type that represents inputs and outputs of a ServiceFunction, represents inputs and outputs of a ServiceSpecification.




Figure 9:82 - ServiceParameter

ServiceSpecificationRole

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#), [InteractionRole](#)

Description

A behavioral feature of a ServiceSpecification whose behavior is specified in a ServiceFunction.




Figure 9:83 - ServiceSpecificationRole

Domain MetaModel::Services::Connectivity

ServiceInterface

Package: Connectivity

isAbstract: No

Generalization: [PropertySet](#)

Description

A contract that defines the ServiceMethods and ServiceMessageHandlers that the ServiceSpecification realizes.




Figure 9:84 - ServiceInterface

ServicePort

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An interaction point for a ServiceSpecification through which it can interact with the outside environment and which is defined by a ServiceInterface.




Figure 9:85 - ServicePort

Domain MetaModel::Services::Processes

ServiceFunction

Package: Processes

isAbstract: No

Generalization: [Process](#)

Description

An Activity that describes the abstract behavior of ServiceSpecifications, regardless of the actual implementation.




Figure 9:86 - ServiceFunction

ServiceFunctionAction

Package: Processes

isAbstract: No

Generalization: [ProcessUsage](#)

Description

A call of a ServiceFunction in the context of another ServiceFunction.




Figure 9:87 - ServiceFunctionAction

ServiceFunctionEdge

Package: Processes

isAbstract: Yes

Generalization: [ProcessEdge](#)

Description

A tuple that shows the flow of Resources (objects/information) between OperationalActivityActions.




Figure 9:88 - ServiceFunctionEdge

Domain MetaModel::Services::States

ServiceStateDescription

Package: States

isAbstract: No

Generalization: [MeasurableElement](#), [StateDescription](#)

Description

A state machine describing the behavior of a ServiceSpecification, depicting how the ServiceSpecification responds to various events and the actions.




Figure 9:89 - ServiceStateDescription

Domain MetaModel::Services::Interaction Scenarios

ServiceInteractionScenario

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionScenario](#)

Description

A specification of the interactions between ServiceSpecifications.




Figure 9:90 - ServiceInteractionScenario

ServiceMessage

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionMessage](#)

Description

Message for use in a Service Event-Trace.




Figure 9:91 - ServiceMessage

Domain MetaModel::Services::Constraints

ServicePolicy

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A constraint governing the use of one or more ServiceSpecifications.




Figure 9:92 - ServicePolicy

Domain MetaModel::Services::Traceability

Consumes

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an OperationalActivity make use of a service.




Figure 9:93 - Consumes

9.1.5 Domain MetaModel::Personnel

Stakeholders: Human resources, Solution Providers, PMs.

Concerns: human factors.

Definition: aims to clarify the role of Human Factors (HF) when creating architectures in order to facilitate both Human Factors Integration (HFI) and systems engineering (SE).

Domain MetaModel::Personnel::Taxonomy

Organization

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A group of OrganizationalResources (Persons, Posts, Organizations and Responsibilities) associated for a particular purpose.




Figure 9:94 - Organization

OrganizationalResource

Package: Taxonomy

isAbstract: Yes

Generalization: [PhysicalResource](#), [Stakeholder](#)

Description

An abstract type for Organization, Person, Post and Responsibility.




Figure 9:95 - OrganizationalResource

Person

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A type of a human being used to define the characteristics that need to be described for ActualPersons (e.g., properties such as address, telephone number, nationality, etc.).




Figure 9:96 - Person

Post

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A type of job title or position that a person can fill (e.g., Lawyer, Solution Architect, Machine Operator or Chief Executive Officer).




Figure 9:97 - Post

Responsibility

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

The type of duty required of a Person or Organization.




Figure 9:98 - Responsibility

Domain MetaModel::Personnel::Structure

PostRole

Package: Structure

isAbstract: No

Generalization: [OrganizationalResource](#), [ResourceRole](#)

Description

A usage of a post in the context of another OrganizationalResource. Creates a whole-part relationship.




Figure 9:99 - PostRole

SubOrganization

Package: Structure

isAbstract: No

Generalization: [OrganizationalResource](#), [ResourceRole](#)

Description

A type of a human being used to define the characteristics that need to be described for ActualPersons (e.g., properties such as address, telephone number, nationality, etc.).




Figure 9:100 - SubOrganization

Domain MetaModel::Personnel::Connectivity

Command

Package: Connectivity

isAbstract: No

Generalization: [ResourceExchange](#)

Description

A type of ResourceExchange that asserts that one OrganizationalResource commands another.




Figure 9:101 - Command

Control

Package: Connectivity

isAbstract: No

Generalization: [ResourceExchange](#)

Description

A type of ResourceExchange that asserts that one PhysicalResource controls another PhysicalResource (i.e., the driver of a vehicle controlling the vehicle speed or direction).




Figure 9:102 - Control

Domain MetaModel::Personnel::Interaction Scenarios

ResourceInteractionScenario

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionScenario](#)

Description

A specification of the interactions between ResourcePerformers in a ResourceArchitecture.




Figure 9:103 - ResourceInteractionScenario

Domain MetaModel::Personnel::Constraints

Competence

Package: Constraints

isAbstract: No

Generalization: [PropertySet](#), [SubjectOfForecast](#)

Description

A specific set of abilities defined by knowledge, skills and aptitude.




Figure 9:104 - Competence

CompetenceForRole

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple used to associate an organizational role with a specific set of required competencies.




Figure 9:105 - CompetenceForRole

RequiresCompetence

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an ActualOrganizationalResource is required to have a specific set of Competencies.




Figure 9:106 - RequiresCompetence

Domain MetaModel::Personnel::Roadmap

FillsPost

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an ActualPerson fills an ActualPost.




Figure 9:107 - FillsPost

Attributes

- endDate : ISO8601DateTime[0..1] End date of an ActualPerson filling an ActualPost.
- startDate : ISO8601DateTime[0..1] Start date of an ActualPerson filling an ActualPost.

Domain MetaModel::Personnel::Traceability

CompetenceToConduct

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple used to associate a Function with a specific set of Competencies needed to conduct the Function.




Figure 9:108 - CompetenceToConduct

9.1.6 Domain MetaModel::Resources

Domain MetaModel::Resources::Taxonomy

CapabilityConfiguration

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

A composite structure representing the physical and human resources (and their interactions) in an enterprise, assembled to meet a capability.




Figure 9:109 - CapabilityConfiguration

NaturalResource

Package: Taxonomy

isAbstract: No

Generalization: [PhysicalResource](#)

Description

Type of physical resource that occurs in nature such as oil, water, gas or coal.




Figure 9:110 - NaturalResource

PhysicalResource

Package: Taxonomy

isAbstract: Yes

Generalization: [ResourcePerformer](#)

Description

An abstract type defining physical resources (i.e., OrganizationalResource, ResourceArtifact and NaturalResource).




Figure 9:111 - PhysicalResource

ResourceArchitecture

Package: Taxonomy

isAbstract: No

Generalization: [ResourcePerformer](#), [Architecture](#)

Description

A type used to denote a model of the Architecture, described from the ResourcePerformer perspective.




Figure 9:112 - ResourceArchitecture

ResourceArtifact

Package: Taxonomy

isAbstract: No

Generalization: [PhysicalResource](#)

Description

A type of man-made object that contains no human beings (i.e., satellite, radio, petrol, gasoline, etc.).




Figure 9:113 - ResourceArtifact

ResourcePerformer

Package: Taxonomy

isAbstract: Yes

Generalization: [ResourceExchangeItem](#), [SubjectOfResourceConstraint](#), [OperationalExchangeItem](#), [SubjectOfForecast](#), [CapableElement](#), [Desirer](#), [VersionedElement](#), [ResourceAsset](#)

Description

An abstract grouping of elements that can perform Functions.




Figure 9:114 – ResourcePerformer

Attributes

isStandardConfiguration : Boolean[] Indicates if the ResourcePerformer is StandardConfiguration, default=false.

Software

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArtifact](#)

Description

A sub-type of ResourceArtifact that specifies an executable computer program.




Figure 9:115 - Software

System

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

An integrated set of elements, subsystems, or assemblies that accomplish a defined objective. These elements include products (hardware, software, firmware), processes, people, information, techniques, facilities, services, and other support elements (INCOSE SE Handbook V4, 2015).




Figure 9:116 - System

Domain MetaModel::Resources::Structure

ResourceMethod

Package: Structure

isAbstract: No

Generalization: [ProcessOperation](#)

Description

A behavioral feature of a ResourcePerformer whose behavior is specified in a Function.




Figure 9:117 - ResourceMethod

ResourceParameter

Package: Structure

isAbstract: No

Generalization: [ProcessParameter](#)

Description

A type that represents inputs and outputs of a Function. It is typed by a ResourceInteractionItem.




Figure 9:118 - ResourceParameter

ResourcePort

Package: Structure

isAbstract: No

Generalization: [ProtocolImplementation](#), [MeasurableElement](#)

Description

An interaction point for a ResourcePerformer through which it can interact with the outside environment and which is defined by a ResourceInterface.




Figure 9:119 - ResourcePort

ResourceRole

Package: Structure

isAbstract: No

Generalization: [SubjectOfResourceConstraint](#), [LocationHolder](#), [AssetRole](#), [InteractionRole](#)

Description

Usage of a ResourcePerformer in the context of another ResourcePerformer. Creates a whole-part relationship.




Figure 9:120 - ResourceRole

Domain MetaModel::Resources::Connectivity

ResourceConnector

Package: Connectivity

isAbstract: No

Generalization: [ProtocolImplementation](#), [MeasurableElement](#)

Description

A channel for exchange between two ResourceRoles.




Figure 9:121 - ResourceConnector

ResourceExchange

Package: Connectivity

isAbstract: No

Generalization: [Exchange](#)

Description

Asserts that a flow can exist between ResourcePerformers (i.e., flows of data, people, material, or energy).




Figure 9:122 - ResourceExchange

ResourceExchangeItem

Package: Connectivity

isAbstract: Yes

Generalization: [Resource](#), [SubjectOfSecurityConstraint](#), [ExchangeItem](#)

Description

An abstract type grouping elements that defines the types of elements that can be exchanged between ResourcePerformers and conveyed by a ResourceExchange.




Figure 9:123 - ResourceExchangeltem

ResourceInterface

Package: Connectivity

isAbstract: No

Generalization: [PropertySet](#)

Description

A declaration that specifies a contract between the ResourcePerformers it is related to and any other ResourcePerformers it can interact with. It is also intended to be an implementation of a specification of an Interface in the Business and/or Service layer.




Figure 9:124 - ResourceInterface

ResourceSignal

Package: Connectivity

isAbstract: No

Generalization: [ResourceExchangeItem](#)

Description

A property of an element representing something in the physical world, expressed in amounts of a unit of measure.




Figure 9:125 - ResourceSignal

Domain MetaModel::Resources::Processes

Function

Package: Processes

isAbstract: No

Generalization: [SubjectOfResourceConstraint](#), [Process](#)

Description

An Activity which is specified in the context to the ResourcePerformer (human or machine) that IsCapableToPerform it.




Figure 9:126 - Function

FunctionAction

Package: Processes

isAbstract: No

Generalization: [ProcessUsage](#)

Description

A call of a Function indicating that the Function is performed by a ResourceRole in a specific context.




Figure 9:127 - FunctionAction

FunctionEdge

Package: Processes

isAbstract: No

Generalization: [ProcessEdge](#)

Description

A tuple that shows the flow of Resources (objects/data) between FunctionActions.




Figure 9:128 - FunctionEdge

Domain MetaModel::Resources::States

ResourceStateDescription

Package: States

isAbstract: No

Generalization: [MeasurableElement](#), [StateDescription](#)

Description

A state machine describing the behavior of a ResourcePerformer, depicting how the ResourcePerformer responds to various events and the actions.




Figure 9:129 - ResourceStateDescription

Domain MetaModel::Resources::Interaction Scenarios

ResourceMessage

Package: Interaction Scenarios

isAbstract: No

Generalization: [InteractionMessage](#)

Description

Message for use in a Resource Event-Trace which carries any of the subtypes of ResourceExchange.




Figure 9:130 - ResourceMessage

Domain MetaModel::Resources::Information

DataElement

Package: Information

isAbstract: No

Generalization: [SubjectOfResourceConstraint](#), [ResourceAsset](#), [ResourceExchangeItem](#)

Description

A formalized representation of data that is managed by or exchanged between resources.




Figure 9:131 - DataElement

DataRole

Package: Information

isAbstract: No

Generalization: [AssetRole](#)

Description

A usage of DataElement that exists in the context of a ResourceAsset. It also allows the representation of the whole-part aggregation of DataElements.




Figure 9:132 - DataRole

Domain MetaModel::Resources::Constraints

ResourceConstraint

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A rule governing the structural or functional aspects of an implementation.



Figure 9:133 - ResourceConstraint

SubjectOfResourceConstraint

Package: Constraints

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping elements that can be the subject of a ResourceConstraint.




Figure 9:134 - SubjectOfResourceConstraint

Domain MetaModel::Resources::Roadmap

Forecast

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that specifies a transition from one Asset, Standard, Competence to another future one. It is related to an ActualEnterprisePhase to give it a temporal context.




Figure 9:135 - Forecast

SubjectOfForecast

Package: Roadmap

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping elements that can be the subject of a Forecast.




Figure 9:136 - SubjectOfForecast

Technology

Package: Roadmap

isAbstract: No

Generalization: [ResourceArtifact](#)

Description

A sub type of ResourceArtifact that indicates a technology domain, i.e., nuclear, mechanical, electronic, mobile telephony etc.




Figure 9:137 - Technology

VersionedElement

Package: Roadmap

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping ResourcePerformer and ServiceSpecification that allows VersionOfConfiguration to be related to ActualProjectMilestones.




Figure 9:138 - VersionedElement

VersionOfConfiguration

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of a WholeLifeConfiguration, used in version control of a VersionedElement. It asserts that a VersionedElement is a version of a WholeLifeConfiguration.




Figure 9:139 - VersionOfConfiguration

VersionSuccession

Package: Roadmap

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between two VersionOfConfigurations that denotes that one VersionOfConfiguration follows from another.




Figure 9:140 - VersionSuccession

WholeLifeConfiguration

Package: Roadmap

isAbstract: No

Generalization: [PropertySet](#)

Description

A set of VersionedElements.




Figure 9:141 - WholeLifeConfiguration

Domain MetaModel::Resources::Traceability

ProtocolImplementation

Package: Traceability

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping architectural elements that can implement Protocols.




Figure 9:142 - ProtocolImplementation

9.1.7 Domain MetaModel::Security

Stakeholders: Security Architects, Security Engineers, Systems Engineers, Operational Architects.

Concerns: addresses the security constraints and information assurance attributes that exist on exchanges between resources and OperationalPerformers

Definition: illustrates the security assets, security constraints, security controls, families, and measures required to address specific security concerns.

Domain MetaModel::Security::Taxonomy

Asset

Package: Taxonomy

isAbstract: Yes

Generalization: [SubjectOfForecast](#), [ConceptItem](#), [LocationHolder](#), [PropertySet](#), [SubjectOfSecurityConstraint](#)

Description

Asset as applied to Security views, an abstract type that indicates the types of elements that can be considered as a subject for security analysis.




Figure 9:143 - Asset

OperationalAsset

Package: Taxonomy

isAbstract: Yes

Generalization: [Asset](#)




Figure 9:144 - OperationalAsset

OperationalMitigation

Package: Taxonomy

isAbstract: No

Generalization: [OperationalArchitecture](#)

Description

A set of OperationalPerformers intended to address against specific operational risks.




Figure 9:145 - OperationalMitigation

ResourceAsset

Package: Taxonomy

isAbstract: Yes

Generalization: [Asset](#)




Figure 9:146 - ResourceAsset

ResourceMitigation

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

A set of ResourcePerformers intended to address against specific risks.




Figure 9:147 - ResourceMitigation

SecurityEnclave

Package: Taxonomy

isAbstract: No

Generalization: [ResourceArchitecture](#)

Description

Collection of information systems connected by one or more internal networks under the control of a single authority and security policy. The systems may be structured by physical proximity or by function, independent of location.




Figure 9:148 - SecurityEnclave

Domain MetaModel::Security::Structure

AssetRole

Package: Structure

isAbstract: Yes

Generalization: BPMN2Metamodel::ResourceRole, [SubjectOfSecurityConstraint](#), [MeasurableElement](#)

Description

AssetRole as applied to Security views, an abstract element that indicates the type of elements that can be considered as a subject for security analysis in the particular context.




Figure 9:149 - AssetRole

InformationRole

Package: Structure

isAbstract: No

Generalization: [AssetRole](#)

Description

A usage of InformationElement that exists in the context of an OperationalAsset. It also allows the representation of the whole-part aggregation of InformationElements.




Figure 9:150 - InformationRole

Domain MetaModel::Security::Processes

EnhancedSecurityControl

Package: Processes

isAbstract: No

Generalization: [SecurityControl](#)

Description

Statement of security capability to: (i) build in additional but related, functionality to a basic control; and/or (ii) increase the strength of a basic control.




Figure 9:151 - EnhancedSecurityControl

Enhances

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating the EnhancedSecurityControl to a SecurityControl.




Figure 9:152 - Enhances

Protects

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a SecurityControl is required to protect an Asset.




Figure 9:153 - Protects

ProtectsInContext

Package: Processes

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that relates a SecurityControlAction to an OperationalRole, or a ResourceRole. It indicates that SecurityControl is required to protect an Asset in a specific context or configuration.




Figure 9:154 - ProtectsInContext

SecurityProcess

Package: Processes

isAbstract: No

Generalization: [OperationalActivity](#), [Function](#), [SubjectOfSecurityConstraint](#)

Description

The security-related procedure that satisfies the security control requirement.




Figure 9:155 - SecurityProcess

SecurityProcessAction

Package: Processes

isAbstract: No

Generalization: [OperationalActivityAction](#), [FunctionAction](#)

Description

A call of a SecurityProcess in the context of another SecurityProcess.




Figure 9:156 - SecurityProcessAction

Domain MetaModel::Security::Constraints

ActualRisk

Package: Constraints

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

An instance of a Risk. A value holder for Risk Measurements.




Figure 9:157 - ActualRisk

Caveat

Package: Constraints

isAbstract: No

Generalization: [SecurityConstraint](#)

Description

A statement that details alternate conditions under which the rule is not valid.




Figure 9:158 - Caveat

Risk

Package: Constraints

isAbstract: No

Generalization: [PropertySet](#)

Description

A statement of the impact of an event on Assets. It represents a constraint on an Asset in terms of adverse effects, with an associated measure. The measure is used to capture the extent to which an entity is threatened by a potential circumstance or event. Risk is typically a function of: (i) the adverse impacts that would arise if the circumstance or event occurs; and (ii) the likelihood of occurrence.




Figure 9:159 - Risk

SecurityAvailability

Package: Constraints

isAbstract: No

Generalization: [SecurityMeasurement](#)

Description

Details the potential impact on organization or individuals if the information is not available to those who need to access it.




Figure 9:160 - SecurityAvailability

SecurityCategory

Package: Constraints

isAbstract: No

Generalization: [MeasurementSet](#)

Description

The security categories that have been determined for each type of information processed, stored, or transmitted by those information systems. The generalized format for expressing the security category (SC) of an information system is:
SC information system = {(confidentiality, impact), (integrity, impact), (availability, impact)}.




Figure 9:161 - SecurityCategory

SecurityClassification

Package: Constraints

isAbstract: No

Generalization: [SecurityMeasurement](#)

Description

Details a classification for the exchange.




Figure 9:162 - SecurityClassification

SecurityClassificationKind

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A type that defines acceptable values for the security category (SC) of an information system, where the acceptable values for potential impact are low, moderate, or high.




Figure 9:163 - SecurityClassificationKind

SecurityConstraint

Package: Constraints

isAbstract: No

Generalization: [Rule](#)

Description

A type of rule that captures a formal statement to define access control policy language.




Figure 9:164 - SecurityConstraint

SecurityControl

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

The management, operational, and technical control (i.e., safeguard or countermeasure) prescribed for an information system to protect the confidentiality, integrity, and availability of the system and its information [NIST SP 800-53].




Figure 9:165 - SecurityControl

SecurityControlFamily

Package: Constraints

isAbstract: No

Generalization: [SecurityControl](#)

Description

An element that organizes security controls into a family. Each Security Control Family contains security controls related to the general security topic of the family.




Figure 9:166 – SecurityControlFamily

SecurityIntegrity

Package: Constraints

isAbstract: No

Generalization: [SecurityMeasurement](#)

Description

Details the potential impact on organization or individuals due to modification or destruction of information, and includes ensuring information non-repudiation and authenticity.




Figure 9:167 - SecurityIntegrity

SecurityMeasurement

Package: Constraints

isAbstract: Yes

Generalization: [Measurement](#)

Description

An abstract type grouping all types of security measurements (e.g., SecurityIntegrity, SecurityAvailability).




Figure 9:168 - SecurityMeasurement

SubjectOfSecurityConstraint

Package: Constraints

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping elements that can be the subject of a SecurityConstraint.




Figure 9:169 - SubjectOfSecurityConstraint

Domain MetaModel::Security::Traceability

Affects

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a Risk is applicable to an Asset.




Figure 9:170 - Affects

AffectsInContext

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that a Risk is applicable to an AssetRole in the specific context or configuration.




Figure 9:171 – AffectsInContext

Mitigates

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating a Security Control to a Risk. Mitigation is established to manage risk and could be represented as an overall strategy or through techniques (mitigation configurations) and procedures (SecurityProcesses).




Figure 9:172 - Mitigates

OwensRisk

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating a Risk to an organizational resource that is responsible for executing the risk mitigation.




Figure 9:173 - OwensRisk

OwensRiskInContext

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple relating a Risk to an organizational role that is responsible for executing the risk mitigation in the specific context or configuration.




Figure 9:174 - OwnsRiskInContext

9.1.8 Domain MetaModel::Projects

Domain MetaModel::Projects::Taxonomy

Project

Package: Taxonomy

isAbstract: No

Generalization: [OrganizationalResource](#)

Description

A type that describes types of time-limited endeavors that are required to meet one or more Capability needs.




Figure 9:175 - Project

ProjectMilestone

Package: Taxonomy

isAbstract: No

Generalization: [PropertySet](#)

Description

A type of event in a Project by which progress is measured.




Figure 9:176 - ProjectMilestone

Domain MetaModel::Projects::Structure

ActualProjectMilestoneRole

Package: Structure

isAbstract: No

Generalization: [ActualState](#)

Description

An ActualProjectMilestone that is applied to a ProjectMilestoneRole.




Figure 9:177 - ActualProjectMilestoneRole

ProjectMilestoneRole

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

The role played by a ProjectMilestone in the context of a Project.




Figure 9:178 - ProjectMilestoneRole

ProjectStatus

Package: Structure

isAbstract: No

Generalization: [ActualState](#)

Description

The status (i.e., level of progress) of a ProjectTheme for an ActualProject at the time of the ActualProjectMilestone.




Figure 9:179 - ProjectStatus

ProjectTheme

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of a ProjectMilestone that captures an aspect by which the progress of ActualProjects may be measured.




Figure 9:180 - ProjectTheme

StatusIndicators

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An enumerated type that specifies a status for a ProjectTheme.




Figure 9:181 - StatusIndicators

Domain MetaModel::Projects::Connectivity

MilestoneDependency

Package: Connectivity

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between two ActualProjectMilestones that denotes one ActualProjectMilestone follows from another.




Figure 9:182 - MilestoneDependency

Domain MetaModel::Projects::Processes

ProjectActivity

Package: Processes

isAbstract: No

Generalization: [Function](#), [Process](#)

Description

An activity carried out during a project.




Figure 9:183 - ProjectActivity

ProjectActivityAction

Package: Processes

isAbstract: No

Generalization: [FunctionAction](#)

Description

The ProjectActivityAction is defined as a call behavior action that invokes the activity that needs to be performed.




Figure 9:184 - ProjectActivityAction

Domain MetaModel::Projects::Interaction Scenarios

ProjectSequence

Package: Interaction Scenarios

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between two ActualProjects that denotes one ActualProject cannot start before the previous ActualProject is finished.




Figure 9:185 - ProjectSequence

Domain MetaModel::Projects::Roadmap

ActualProject

Package: Roadmap

isAbstract: No

Generalization: [ActualOrganizationalResource](#), [Achiever](#)

Description

A time-limited endeavor to provide a specific set of ActualResources that meet specific Capability needs.




Figure 9:186 – ActualProject

ActualProjectMilestone

Package: Roadmap

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

An event with a start date in an ActualProject from which progress is measured.




Figure 9:187 - ActualProjectMilestone

Constraints

[1] unnamed1 startTime=endTime

Domain MetaModel::Projects::Traceability

ResponsibleFor

Package: Traceability

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple between an ActualResponsibleResource and an ActualResponsibility or ActualProject. It defines the duties that the ActualResponsibleResource is ResponsibleFor.




Figure 9:188 – ResponsibleFor

9.1.9 Domain MetaModel::Standards

Stakeholders: Solution Providers, Systems Engineers, Software Engineers, Systems Architects, Business Architects.

Concerns: technical and non-technical Standards applicable to the architecture.

Definition: shows the technical, operational, and business Standards applicable to the architecture. Defines the underlying current and expected Standards.

Domain MetaModel::Standards::Taxonomy

Protocol

Package: Taxonomy

isAbstract: No

Generalization: [Standard](#)

Description

A Standard for communication over a network. Protocols may be composite, represented as a ProtocolStack made up of ProtocolLayers.




Figure 9:189 - Protocol

ProtocolStack

Package: Taxonomy

isAbstract: No

Generalization: [Protocol](#)

Description

A sub type of Protocol that contains the ProtocolLayers, defining a complete stack.




Figure 9:190 - ProtocolStack

Standard

Package: Taxonomy

isAbstract: No

Generalization: [SubjectOfForecast](#), [PropertySet](#)

Description

A ratified and peer-reviewed specification that is used to guide or constrain the architecture. A Standard may be applied to any element in the architecture.




Figure 9:191 - Standard

Attributes

mandatedDate : ISO8601DateTime[0..1] The date when this version of the Standard was published.

retiredDate : ISO8601DateTime[0..1] The date when this version of the Standard was retired.

Domain MetaModel::Standards::Structure

ProtocolLayer

Package: Structure

isAbstract: No

Generalization: [MeasurableElement](#)

Description

Usage of a Protocol in the context of another Protocol. Creates a whole-part relationship.




Figure 9:192 – ProtocolLayer

9.1.10 Domain MetaModel::Actual Resources

Stakeholders: Solution Providers, Systems Engineers, Business Architects, Human Resources.

Concerns: the analysis.e.g., evaluation of different alternatives, what-if, trade-offs, V&V on the actual resource configurations.

Definition: illustrates the expected or achieved actual resource configurations and actual relationships between them.

Domain MetaModel::Actual Resources::Taxonomy

ActualOrganization

Package: Taxonomy

isAbstract: No

Generalization: [ActualResponsibleResource](#)

Description

An actual formal or informal organizational unit, e.g., "Driving and Vehicle Licensing Agency", "UAF team Alpha".




Figure 9:193 - ActualOrganization

Attributes

- serviceType : String[0..1] Service office code or symbol
- shortName : String[0..1] String providing a simplified means of identifying an ActualOrganization, i.e. SoftWareGroup could use SWG as the shortName.

ActualOrganizationalResource

Package: Taxonomy

isAbstract: Yes

Generalization: [ActualResource](#), [Stakeholder](#)

Description

Abstract element for an ActualOrganization, ActualPerson or ActualPost.




Figure 9:194 - ActualOrganizationalResource

ActualPerson

Package: Taxonomy

isAbstract: No

Generalization: [ActualResponsibleResource](#)

Description

An individual human being.




Figure 9:195 – ActualPerson

ActualPost

Package: Taxonomy

isAbstract: No

Generalization: [ActualResponsibleResource](#)

Description

An actual, specific post, an instance of a Post "type" - e.g., "President of the United States of America." where the Post would be president.




Figure 9:196 - ActualPost

ActualResource

Package: Taxonomy

isAbstract: No

Generalization: [ActualPropertySet](#), [SubjectOfResourceConstraint](#), [Achiever](#), [CapableElement](#)

Description

An individual, fully-realized ResourcePerformer.




Figure 9:197 – ActualResource

ActualResourceRelationship

Package: Taxonomy

isAbstract: No

Generalization: [UAFElement](#)

Description

An actual resource flow existing between ActualResources (i.e., flow of data, people, materiel, or energy).




Figure 9:198 - ActualResourceRelationship

ActualResponsibility

Package: Taxonomy

isAbstract: No

Generalization: [ActualOrganizationalResource](#)

Description

An actual duty required of a Person or Organization.




Figure 9:199 – ActualResponsibility

ActualResponsibleResource

Package: Taxonomy

isAbstract: Yes

Generalization: [ActualOrganizationalResource](#)

Description

An abstract type grouping responsible OrganizationalResources.




Figure 9:200 - ActualResponsibleResource

FieldedCapability

Package: Taxonomy

isAbstract: No

Generalization: [ActualResource](#)

Description

An individual, fully-realized capability.




Figure 9:201 - FieldedCapability

Domain MetaModel::Actual Resources::Constraints

ActualService

Package: Constraints

isAbstract: Yes

Generalization: [ActualMeasurementSet](#), [CapableElement](#)

Description

An individual ServiceSpecification.




Figure 9:202 - ActualService

ProvidedServiceLevel

Package: Constraints

isAbstract: No

Generalization: [ActualService](#)

Description

A sub type of ActualService that details a specific service level delivered by the provider.




Figure 9:203 - ProvidedServiceLevel

ProvidesCompetence

Package: Constraints

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that an ActualOrganizationalResource provides a specific set of Competencies.




Figure 9:204 - ProvidesCompetence

RequiredServiceLevel

Package: Constraints

isAbstract: No

Generalization: [ActualService](#)

Description

A sub type of ActualService that details a specific service level required of the provider.




Figure 9:205 - RequiredServiceLevel

9.1.11 Domain MetaModel::Dictionary

Stakeholders: Architects, users of the architecture, Capability Owners, Systems Engineers, Solution Providers.

Concerns: Definitions for all the elements in the architecture, libraries of environments and measurements.

Definition: Presents all the elements used in an architecture. Can be used specifically to capture:

- Elements and relationships that are involved in defining the environments applicable to capability, operational concept or set of systems.
- Measurable properties that can be used to support analysis such as KPIs, MoEs, TPIs etc.

Recommended Implementation: Tabular format, SysML Block Definition Diagram.

Alias

Package: Dictionary

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A metamodel Artifact used to define an alternative name for an element.




Figure 9:206 – Alias

Attributes

nameOwner : String[*] Someone or something that uses this alternative name.

Definition

Package: Dictionary

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A comment containing a description of an element in the architecture.




Figure 9:207 - Definition

Attributes

author : String[*] The original or current person (architect) responsible for the Definition.

SameAs

Package: Dictionary

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A tuple that asserts that two elements refer to the same real-world thing.




Figure 9:208 – SameAs

9.1.12 Domain MetaModel::Summary & Overview

ArchitecturalDescription

Package: Summary & Overview

isAbstract: No

Generalization: [MeasurableElement](#)

Description

An Architecture Description is a work product used to express the Architecture of some System Of Interest.

It provides executive-level summary information about the architecture description in a consistent form to allow quick reference and comparison between architecture descriptions -- It includes assumptions, constraints, and limitations that may affect high-level decisions relating to an architecture-based work program.




Figure 9:209 - ArchitecturalDescription

Attributes

approvalAuthority : String[*]	Someone or something that has the authority to approve the ArchitecturalDescription.
architect : String[*]	Someone responsible for the creation of ArchitecturalDescription.
assumptionAndConstraint : String[*]	Any assumptions, constraints, and limitations contained in the ArchitecturalDescription, including those affecting deployment, communications performance, information assurance environments, etc.
creatingOrganization : String[*]	The organization responsible for creating the ArchitecturalDescription.
dateCompleted : String[0..1]	Date that the ArchitecturalDescription was completed.
methodologyUsed : String[*]	The methodology used in developing the architecture.
purpose : String[*]	Explains the need for the Architecture, what it will demonstrate, the types of analyses that will be applied to it, who is expected to perform the analyses, what decisions are expected to be made on the basis of each form of analysis, who is expected to make those decisions, and what actions are expected to result.

recommendations : String[*]	States the recommendations that have been developed based on the architecture effort. Examples include recommended system implementations, and opportunities for technology insertion.
status : String[*]	Approval status of the architecture.
summaryOfFindings : String[*]	Summarizes the findings that have been developed so far. This may be updated several times during the development of the ArchitecturalDescription.
toBe : Boolean[1]	Indicates whether the ArchitecturalDescription represents an Architecture that exists or will exist in the future.
toolsUsed : String[*]	Identifies any tools used to develop the ArchitecturalDescription as well as file names and formats if appropriate.
version : String[*]	Version number of the architecture.

Architecture

Package: Summary & Overview

isAbstract: Yes

Generalization: [UAFElement](#)
Description

An abstract type that represents a generic architecture. Subtypes are OperationalArchitecture and PhysicalArchitecture.




Figure 9:210 - Architecture

Concern

Package: Summary & Overview

isAbstract: No

Generalization: [PropertySet](#)

Description

Interest in an EnterprisePhase (EnterprisePhase is synonym for System in ISO 42010) relevant to one or more of its stakeholders.




Figure 9:211 - Concern

Stakeholder

Package: Summary & Overview

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Individual, team, organization, or classes thereof, having an interest in an EnterprisePhase [ISO/IEC/IEEE 42010:2011].




Figure 9:212 - Stakeholder

UAFElement

Package: Summary & Overview

isAbstract: Yes

Description

Abstract super type for all of the UAF elements. It provides a way for all of the UAF elements to have a common set of properties.




Figure 9:213 - UAFElement

Attributes

URI : String[0..1] Captures Unique identifier for the element.

View

Package: Summary & Overview

isAbstract: No

Generalization: [PropertySet](#)

Description

An architecture view expresses the architecture of the system-of-interest in accordance with an architecture viewpoint (or simply, viewpoint). [ISO/IEC/IEEE 42010:2011(E)].




Figure 9:214 - View

Viewpoint

Package: Summary & Overview

isAbstract: No

Generalization: [PropertySet](#)

Description

An architecture viewpoint frames (to formulate or construct in a particular style or language) one or more concerns. A concern can be framed by more than one viewpoint. [ISO/IEC/IEEE 42010:2011(E)].




Figure 9:215 - Viewpoint

Attributes

- language : String[*] The languages used to express the Viewpoint.
- method : String[*] The methods employed in the development of the Viewpoint.
- purpose : String[0..1] The purpose of the Viewpoint.

9.1.13 Domain MetaModel::Information

DataModel

Package: Information

isAbstract: No

Generalization: [SubjectOfOperationalConstraint](#), [SubjectOfResourceConstraint](#)

Description

A structural specification of data types, showing relationships between them. The type of data captured in the DataModel is described using the enumeration DataModelKind (Conceptual, Logical and Physical).




Figure 9:216 - DataModel

9.1.14 Domain MetaModel::Parameters

ActualCondition

Package: Parameters

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

An individual describing an actual situation with respect to circumstances under which an OperationalActivity, Function or ServiceFunction can be performed.




Figure 9:217 - ActualCondition

ActualEnvironment

Package: Parameters

isAbstract: No

Generalization: [ActualCondition](#)

Description

An individual that describes the circumstances of an Environment.



Figure 9:218 - ActualEnvironment

ActualLocation

Package: Parameters

isAbstract: No

Generalization: [ActualCondition](#)

Description

An individual that describes a physical location, for example using text to provide an address, Geo-coordinates, etc.




Figure 9:219 - ActualLocation

Attributes

address : String[0..1]

String describing the address of the ActualLocation, i.e. "1600 Pennsylvania avenue", "The White House"

customKind : String[0..1]

String describing a location kind that is not in the LocationKind enumerated list

locationNamedByAddress : Boolean[]

Boolean that indicates if the ActualLocation address is embedded in the ActualLocation name. By default = false.

ActualMeasurement

Package: Parameters

isAbstract: No

Generalization: [ActualState](#)

Description

An actual value that is applied to a Measurement.




Figure 9:220 - ActualMeasurement

ActualMeasurementSet

Package: Parameters

isAbstract: No

Generalization: [ActualPropertySet](#)

Description

A set of ActualMeasurements.




Figure 9:221 - ActualMeasurementSet

ActualPropertySet

Package: Parameters

isAbstract: No

Generalization: [ActualState](#)

Description

A set or collection of Actual properties.




Figure 9:222 - ActualPropertySet

ActualState

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract element that applies temporal extent to a set of elements realized as Instance Specifications.




Figure 9:223 - ActualState

Attributes

endDate : ISO8601DateTime[0..1] End time for all individual elements.

startDate : ISO8601DateTime[0..1] Start time for all individual elements.

Condition

Package: Parameters

isAbstract: No

Generalization: [PropertySet](#)

Description

A type that defines the Location, Environment and/or GeoPoliticalExtent.




Figure 9:224 - Condition

Environment

Package: Parameters

isAbstract: No

Generalization: [Condition](#)

Description

A definition of the environmental factors in which something exists or functions. The definition of an Environment element can be further defined using EnvironmentKind.




Figure 9:225 - Environment

GeoPoliticalExtentType

Package: Parameters

isAbstract: No

Generalization: [Condition](#), [OperationalExchangeItem](#), [ResourceExchangeItem](#)

Description

A type of geospatial extent whose boundaries are defined by declaration or agreement by political parties.




Figure 9:226 - GeoPoliticalExtentType

Attributes

customKind : String[] Captures the kind of GeopoliticalExtentType.

ISO8601DateTime

Package: Parameters

isAbstract: No

Generalization: [UAFElement](#)

Description

A date and time specified in the ISO8601 date-time format including timezone designator (TZD): YYYY-MM-DDThh:mm:ssTZD.




Figure 9:227 - ISO8601DateTime

Location

Package: Parameters

isAbstract: No

Generalization: [ConceptItem](#), [Condition](#)

Description

A specification of the generic area in which a LocationHolder is required to be located.




Figure 9:228 - Location

Attributes

customKind : String[0..1] Captures the kind of Location if the LocationTypeKind has been set to "OtherType".

LocationHolder

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract type, used to group elements that are allowed to be associated with a Location.




Figure 9:229 - LocationHolder

MeasurableElement

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

Abstract type, grouping elements that can be measured by applying MeasurementSets to them.




Figure 9:230 - MeasurableElement

Measurement

Package: Parameters

isAbstract: No

Generalization: [MeasurableElement](#)

Description

A property of an element representing something in the physical world, expressed in amounts of a unit of measure.




Figure 9:231 - Measurement

MeasurementSet

Package: Parameters

isAbstract: No

Generalization: [PropertySet](#)

Description

A collection of Measurements.




Figure 9:232 - MeasurementSet

PropertySet

Package: Parameters

isAbstract: Yes

Generalization: [UAFElement](#)

Description

An abstract type grouping architectural elements that can own Measurements.




Figure 9:233 - PropertySet